

# County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 2,  
T. 32 S., R. 7 W., Willamette Meridian, Oregon

17570

CHAINS

C  $\frac{E\ 1/16}{S\ 2}$  C  
1982

from which

A fir, 11 ins. diam., bears N. 41 3/4° E., 77 lks.  
dist., mkd. CE 1/16 S2 BT.

A fir, 30 ins. diam., bears N. 49° W., 132 lks.  
dist., mkd. CE 1/16 S2 BT.

Descend 350 ft. over SW. slope.

39.70 The center 1/4 sec. cor. of sec. 2.

Descend 100 ft. over SW. slope.

51.10 Gravelled road, 15 lks. wide, bears N. 25° W. and  
S. 20° E.

52.00 Buck Creek, 12 lks. wide, course N. 35° W.; asc. 455 ft.  
over broken NE. slope.

65.70 Gravelled road, 15 lks. wide, bears N. and S. 25° E., in  
a curve.

79.48 The 1/4 sec. cor. of secs. 2 and 3, monumented with an iron  
post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above  
ground, with brass cap mkd.

T 32 S      R 7 W  
          1/4  
          |  
          S 3    S 2  
          1964

from which the remains of a bearing tree mkd. by Beck

A root hole, bears N. 45° W., 55 lks. dist.,  
with a down fir alongside, 6 ins. diam., with  
fragmentary scribe marks visible on decayed  
blaze.

and new bearing trees

A fir, 8 ins. diam., bears S. 31° W., 49 lks.  
dist., mkd. X BT.

A fir, 8 ins. diam., bears N. 70 1/2° W., 24 lks.  
dist., mkd. 1/4 S3 BT.

No suitable trees available within limits in sec. 2.

From the center E 1/16 sec. cor. of sec. 2.

N. 0° 43' W., on the N. and S. center line of the NE 1/4 of  
sec. 2.

Ascend 155 ft. over broken SW. slope, through heavy  
timber and dense undergrowth.

15.20 Ridge, bears N. 35° W. and S. 35° E.; desc. 120 ft. over  
broken NE. slope.