

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of
a Portion of the Subdivisional Lines, 17576
T 32 S R 7 W Willamette Meridian, Oregon

CHAINS

A fir, 10 ins. diam., bears S. 84 1/4° W., 16 lks. dist., mkd. S 1/16 S32 BT.


Descend over NW. slope.

33.90

Ravine, drains S. 55° W.; asc. over SE. slope.

43.59

The 1/4 sec. cor. of secs. 32 and 33, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.



from which the remains of an original bearing tree

A black oak, 24 ins. diam., bears N. 23 3/4° W., 56 lks. dist., no marks visible on open, decayed blaze. (Record, N. 36° W.)

and bearing trees mkd. by Gawron

A fir, 14 ins. diam., bears S. 67 3/4° E., 33 1/2 lks. dist., with healed blaze. (Record, S. 69° E.)

A fir, 10 ins. diam., bears S. 21° W., 43 lks. dist., with healed blaze. (Record, S. 22° W.)

N. 3° 22' W., beginning new measurement.

Ascend over broken SW. slope.


8.40

Spur, slopes W.; desc. over NW. slope.

20.055

Point for the N 1/16 sec. cor. of secs. 32 and 33.

Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.



from which

A fir, 15 ins. diam., bears S. 15 3/4° E., 46 1/2 lks. dist., mkd. N 1/16 S33 BT.

A fir, 14 ins. diam., bears N. 11 1/4° W., 16 1/2 lks. dist., mkd. N 1/16 S32 BT.

Descend over NW. slope.

22.30

Ravine, drains S. 85° W.; asc. over SW. slope.

27.70

Spur, slopes S. 75° W.; desc. over NW. slope.

30.10

Ravine, drains S. 80° W.; asc. over SW. slope.

40.11

Point for the cor. of secs. 28, 29, 32, and 33, at proportionate distance; there is no remaining evidence of the original cor.