

# County Surveyor's Record, Douglas County, Oregon

17579

Dependent Resurvey of  
a Portion of the Subdivisional Lines,  
T. 33 S., R. 6 W., Willamette Meridian, Oregon

CHAINS									
13.70	Same road, bears N. 40° E. and S. 40° W.								
18.80	Ravine, drains S. 30° W.; asc. over SE. slope.								
19.50	Same road, bears SE. and S. 70° W., in curve.								
26.80	Spur, slopes S. 50° W.; desc. over NW. slope.								
29.40	Ravine, drains S. 55° W.; desc. over SE. slope.								
<del>29.40</del>	<del>Ravine, drains S. 55° W.; asc. over SE. slope.</del>								
40.05	<p>Point for the 1/4 sec. cor. of secs. 28 and 29, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T 33 S</td> <td style="padding: 0 10px;">R 6 W</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 0 10px;">1/4</td> </tr> <tr> <td style="padding: 0 10px;">S 29</td> <td style="padding: 0 10px;">S 28</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 0 10px;">1982</td> </tr> </table> </div> <p>from which</p> <p style="margin-left: 40px;">A ponderosa pine, 21 ins. diam., bears N. 81 3/4° E., 71 lks. dist., mkd. 1/4 S28 BT.</p> <p style="margin-left: 40px;">A fir, 17 ins. diam., bears S. 64 1/4° W., 13 lks. dist., mkd. 1/4 S29 BT.</p> <p>Ascend over SE. slope.</p>	T 33 S	R 6 W	1/4		S 29	S 28	1982	
T 33 S	R 6 W								
1/4									
S 29	S 28								
1982									
45.90	Ridge, bears N. 70° W. and S. 70° E.; desc. over broken NE. slope.								
80.10	<p>The cor. of secs. 20, 21, 28, and 29, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T 33 S</td> <td style="padding: 0 10px;">R 6 W</td> </tr> <tr> <td style="padding: 0 10px;">S 20</td> <td style="padding: 0 10px;">S 21</td> </tr> <tr> <td style="padding: 0 10px;">S 29</td> <td style="padding: 0 10px;">S 28</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 0 10px;">1976</td> </tr> </table> </div> <p>from which the remains of the original bearing trees</p> <p style="margin-left: 40px;">A fir, 45 ins. diam., bears N. 35 3/4° E., 122 lks. dist., no marks visible on opened and burned blaze. (Record, N. 38° E., 120 lks.)</p> <p style="margin-left: 40px;">A decayed fir stump, 47 ins. diam., bears S. 40 1/4° E., 131 1/2 lks. dist., no marks visible. (Record, S. 42° E., 128 lks.)</p> <p style="margin-left: 40px;">A decayed fir stump, size indeterminate, bears S. 85° W., 65 lks. dist., no marks visible.</p> <p>and bearing trees mkd. by Gerald D. Riley, Registered Land Surveyor, No. 705, in 1975</p> <p style="margin-left: 40px;">A fir, 17 ins. diam., bears N. 57 1/2° E., 38 lks. dist., with healed double blaze.</p> <p style="margin-left: 40px;">A madrone, 13 ins. diam., bears S. 26° E., 30 lks. dist., with scribe marks S28 R S 705 BT visible on open double blaze.</p>	T 33 S	R 6 W	S 20	S 21	S 29	S 28	1976	
T 33 S	R 6 W								
S 20	S 21								
S 29	S 28								
1976									