

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of
a Portion of the Subdivisional Lines, **17580**
T. 33 S., R. 6 W., Willamette Meridian, Oregon

| CHAINS | |
|--------|---|
| | <p style="text-align: center;">A fir, 10 ins. diam., bears N. 78 3/4° W., 50 lks. dist., with healed double blaze. (Record, N. 78° W.)</p> <p style="text-align: center;">and bearing trees mkd. by Aanrud</p> <p style="text-align: center;">A fir, 16 ins. diam., bears S. 65 1/2° W., 53 lks. dist., with healed blaze.</p> <p>Land, mountainous. Soil, rocky clay. Timber, pine, fir, cedar, oak, chinquapin, and madrone; undergrowth, poison oak, Oregon grape, manzanita, blackberry, ceanothus, salal, young timber, grass, and weeds.</p> |
| | <p>From the cor. of secs. 28, 29, 32, and 33.</p> <p>N. 89° 29' W., bet. secs. 29 and 32.</p> <p>Descend over SW. slope, through heavy timber and dense undergrowth.</p> |
| 6.00 | Ravine, drains S. 5° W.; asc. over SE. slope. |
| 8.10 | Spur, slopes S.; desc. over W. slope. |
| 17.10 | Ravine, drains S. 20° W.; asc. over SE. slope. |
| 20.275 | <p>Point for the E 1/16 sec. cor. of secs. 29 and 32.</p> <p>Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">E 1/16 $\frac{S\ 29}{S\ 32}$</p> <p style="text-align: center;">1982</p> <p>from which</p> <p style="text-align: center;">A fir, 20 ins. diam., bears N. 71 1/4° E., 107 1/2 lks. dist., mkd. E 1/16 S29 BT.</p> <p style="text-align: center;">A fir, 19 ins. diam., bears S. 9 3/4° W., 68 1/2 lks. dist., mkd. E 1/16 S32 BT.</p> <p>Ascend over SE. slope.</p> |
| 29.20 | Spur, slopes S. 35° W.; desc. over W. slope. |
| 33.20 | Ravine, drains S. 85° W.; asc. along broken S. slope. |
| 40.55 | <p>The 1/4 sec. cor. of secs. 29 and 32, perpetuated and recorded by Leland P. Lovejoy, Registered Land Surveyor, No. 262, in 1952, from parole evidence, and is accepted as the best available evidence of the position of the original cor., monumented with an iron pipe, 2 ins. diam., firmly set, projecting 7 ins. above ground.</p> <p>At the corner point</p> <p>Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 7 ins in the ground, directly over the iron pipe, to solid rock, and in a mound of stone, 3 ft. base, to top, with aluminum cap mkd.</p> |