

County Surveyor's Record, Douglas County, Oregon

17581

Dependent Resurvey of
a Portion of the Subdivisional Lines,
T. 33 S., R. 6 W., Willamette Meridian, Oregon

CHAINS

T 33 S R 6 W

1/4 $\frac{S 29}{S 32}$

1982

from which

A white oak, 7 ins. diam., bears N. 64 1/2° E.,
61 1/2 lks. dist., mkd. 1/4 S29 BT.

A fir, 16 ins. diam., bears S. 4 3/4° W.,
91 1/2 lks. dist., mkd. 1/4 S32 BT.

N. 89° 47' W., beginning new measurement.

Ascend along S. slope.

- 4.70 Top of ascent, slopes S.; desc. over broken SW. slope.
- 9.40 Ravine, drains N. 15° W.; asc. over broken NE. slope.
- 17.40 Spur, slopes N. 10° E.; desc. over NW. slope.
- 19.30 Ravine, drains N. 5° W.; asc. over broken NE. slope.
- 26.10 Spur, slopes S.; desc. over W. slope.
- 30.60 Ravine, drains N.; asc. over broken NE. slope.
- 36.81 The cor. of secs. 29, 30, 31, and 32, monumented with an
iron post, 2 1/2 ins. diam., firmly set, projecting 5 ins.
above ground, with brass cap mkd.

T 33 S R 6 W
S 30 | S 29
S 31 | S 32

1958

from which the remaining original bearing trees

A madrone, 33 ins. diam., bears N. 5° E., 40 lks.
dist., with scribe marks S29 visible on open
blaze.

A fir, 36 ins. diam., bears S. 65° W., 12 lks.
dist., with scribe marks T33S R6W S31 BT visible
on bark blaze.

and bearing trees mkd. by Gawron and Thielsen

A fir, 15 ins. diam., bears N. 65 1/4° E., 36 lks.
dist., with healed blaze. (Record, N. 66° E.)

A madrone, 10 ins. diam., bears S. 18° E., 61 lks.
dist., no marks visible.

A madrone, 10 ins. diam., bears S. 72 1/2° W., 36 lks.
dist., with scribe marks T33S R6W S31 BT visible
on open blaze. (Record, S. 71° W.)

A fir, 11 ins. diam., bears N. 29 1/2° W., 52 lks.
dist., with healed blaze.