

County Surveyor's Record, Douglas County, Oregon

17583

Dependent Resurvey of
a Portion of the Subdivisional Lines,
T. 33 S., R. 6 W., Willamette Meridian, Oregon

CHAINS

from which

A fir, 10 ins. diam., bears N. 22 3/4° E., 70 lks. dist., mkd. W 1/16 S20 BT.

A fir, 10 ins. diam., bears S. 56° E., 74 lks. dist., mkd. W 1/16 S29 BT.

Descend over broken NW. slope.

37.00

Irrigation ditch, 8 lks. wide, bears N. 45° E. and S. 35° W.

39.72

The cor. of secs. 19, 20, 29, and 30, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.

| | |
|--------|-------|
| T 33 S | R 6 W |
| S 19 | S 20 |
| S 30 | S 29 |

1963

from which the remains of the original bearing trees

A sawed fir stump, 9 ins. diam., bears N. 51° E., 58 lks. dist., with scribe marks S20 BT visible on open blaze. (Record, N. 50° E.)

A sawed fir stump, 50 ins. diam., bears S. 24° E., 25 lks. dist., with scribe marks BT visible on bark blaze. (Record, S. 26° E.)

A sawed fir stump, 48 ins. diam., bears S. 9 1/4° W., 60 lks. dist., with scribe marks 30 BT visible on bark blaze. (Record, S. 8° W.)

and bearing trees mkd. by Gawron

A fir, 16 ins. diam., bears N. 39 1/2° E., 45 lks. dist., with healed blaze. (Record, N. 40° E.)

A fir, 11 ins. diam., bears S. 64° E., 41 lks. dist., with healed blaze. (Record, S. 63° E.)

A fir, 14 ins. diam., bears S. 11 1/2° W., 55 1/2 lks. dist., with healed blaze.

A fir, 15 ins. diam., bears N. 71° W., 21 1/2 lks. dist., with healed blaze.

Land, mountainous.

Soil, rocky clay.

Timber, pine, fir, cedar, oak, maple, alder, chinquapin, and madrone; undergrowth, poison oak, Oregon grape, manzanita, cenothus, blackberry, salal, young timber, grass, and weeds.

N. 0° 58' W., bet. secs. 19 and 20.

Descend over N. slope, through heavy timber and dense undergrowth.

1.20

Trail, 5 lks. wide, bears NE. and SW.

2.60

Wolf Creek, 30 lks. wide, course S. 60° W.; asc. over SE. slope.