

# County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of  
a Portion of the Subdivisional Lines,  
T. 33 S., R. 6 W., Willamette Meridian, Oregon 17586

**CHAINS**

Land, mountainous.  
Soil, rocky clay.  
Timber, pine, fir, cedar, oak, maple, alder, chinquapin,  
and madrone; undergrowth, poison oak, Oregon grape,  
manzanita, ceanothus, blackberry, salal, grass, and  
weeds.

From the cor. of secs. 16, 17, 20, and 21, perpetuated and  
recorded by R. L. Templin, County Surveyor, in 1971,  
monumented with an iron post, 1 1/2 ins. diam., firmly set,  
projecting 6 ins. above ground, with brass cap mkd.

County Surveyor	
T 33 S	R 6 W
17	16
20	21

from which the remaining original bearing trees

A black oak, 14 ins. diam., bears S. 21° E.,  
16 lks. dist., no marks visible on open decayed  
blaze. (Record, S. 34° E.)

A madrone, 14 ins. diam., bears S. 48° W.,  
77 lks. dist., no marks visible on open blaze.

A fir, 35 ins. diam., bears N. 30° W., 28 lks.  
dist., with healed blaze. (Record, N. 32° W.,  
30 lks. dist.)

and bearing trees marked by Templin

A black oak, 12 ins. diam., bears N. 42° E.,  
22 1/2 lks. dist., with healed double blaze.

A fir, 12 ins. diam., bears S. 45° W., 33 1/2 lks.  
dist., with healed double blaze.

N. 88° 57' W., bet. secs. 17 and 20.

Ascend over broken SE. slope.

9.10 Spur, slopes S. 30° W.; asc. over broken SE. slope.

10.90 Spur ridge, slopes S. 15° W.; desc. over NW. slope.

32.10 Ravine, drains S.; asc. over SE. slope.

35.00 Ridge, bears N. 40° E. and S. 40° W.; desc. over  
NW. slope.

39.77 Point for the 1/4 sec. cor. of secs. 17 and 20, at propor-  
tionate distance; there is no remaining evidence of the  
original corner.

Set an aluminum post, 28 ins. long, 2 1/2 ins. diam.,  
24 ins. in the ground, with aluminum cap mkd.

T 33 S		R 6 W	
1/4	S 17		
	S 20		
1982			

from which