

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines, **17594**
 T. 22 S., R. 5 W., Willamette Meridian, Oregon

CHAINS

from which

A fir, 16 ins. diam., bears N. 30 1/2° E., 33 1/2 lks. dist., mkd. 1/4 S1 BT.

A fir, 11 ins. diam., bears S. 5° E., 35 lks. dist., mkd. 1/4 S12 BT.

From this point, a cor. established by Blaine H. McGillicuddy, Registered Engineer, No. 2066, in 1952, bears N. 58° 04' E., 0.50 chs. dist., monumented with a mound of stone, 2 ft. base, 1 ft. high, from which bearing trees mkd. by McGillicuddy

A sawed fir stump, 22 ins. diam., bears S. 56 1/2° E., 68 lks. dist., with axe marks visible on an opened blaze.

A fir, 45 ins. diam., bears N. 33° W., 123 lks. dist., with a healed blaze.


Descend over SW. slope.

57.25 Wehmeyer Creek, 5 lks. wide, course S. 40° W.; asc. over SE. slope.

78.34 Creek, 3 lks. wide, course S. 40° E.; asc. over NE. slope.

80.52 The cor. of secs. 1, 2, 11, and 12, perpetuated and recorded by James W. Byron, Deputy Douglas County Surveyor, in 1958, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE



R 5 W

1958

from which the remains of two original bearing trees

A hemlock, 33 ins. diam., bears S. 43° E., 43 lks. dist., with fragmentary scribe marks visible on an opened blaze.

A root hole, bears N. 19° W., 45 lks. dist., with a down fir alongside, 50 ins. diam., with fragmentary scribe marks visible on an opened blaze.

and bearing trees mkd. by Byron

A fir, 33 ins. diam., bears N. 73 1/2° E., 54 lks. dist., with a healed blaze.

A hemlock, 23 ins. diam., bears S. 79 1/2° W., 37 1/2 lks. dist., with a healed blaze.

A hemlock, 19 ins. diam., bears N. 27° W., 2 1/2 lks. dist., with a healed blaze.