

County Surveyor's Record, Douglas County, Oregon

17600

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 23 S., R. 7 W., Willamette Meridian, Oregon

CHAINS
67.95

Left bank, Umpqua River, edge bears S. 40° E. and N. 55° W., course N. 45° W.

68.56

Point for the meander cor. of secs. 31 and 32, on the left bank of the Umpqua River, at proportionate distance; there is no remaining evidence of the original corner. No permanent monument established.

77.10

Right bank, Umpqua River, edge bears S. 45° E. and N. 45° W.

78.215

Point for the meander cor. of secs. 31 and 32, on the right bank of the Umpqua River, at proportionate distance; there is no remaining evidence of the original corner. No permanent monument established.

80.22

Point for the cor. of secs. 29, 30, 31, and 32, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron pipe, 24 ins. long, 3/4 in. diam., 48 ins. in the ground, with the top 24 ins. below the surface, from which

An iron post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 16° E., 164 lks. dist., with brass cap mkd. T23S R7W S32 RM 1982 with an arrow pointing to the cor.

An iron post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 63 1/2° W., 91 lks. dist., with brass cap mkd. T23S R7W S31 RM 1982 with an arrow pointing to the cor.

An iron post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 61° W., 323 lks. dist., with brass cap mkd. T23S R7W S30 RM 1982 with an arrow pointing to the cor.

The cor. is located in a tree seedling farm.

From this point, the cor. of secs. 19, 20, 29, and 30, bears N. 0° 34' W., 80.22 chs. dist., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.

T 23 S	R 7 W
S 19	S 20
S 30	S 29
1979	

from which the bearing trees mkd. by Wofford

A fir, 18 ins. diam., bears N. 25° E., 25 lks. dist., with fragmentary scribe marks visible on a partially healed blaze.

A fir, 18 ins. diam., bears S. 86 1/4° E., 76 lks. dist., with fragmentary scribe marks visible on a partially healed blaze.

A fir, 15 ins. diam., bears S. 80 3/4° W., 27 lks. dist., with fragmentary scribe marks visible on a partially healed blaze.

A fir, 13 ins. diam., bears N. 83 1/4° W., 41 lks. dist., with a healed blaze.