

County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 31,
T. 23 S., R. 7 W., Willamette Meridian, Oregon

17602

CHAINS	
	From the 1/4 sec. cor. of secs. 31 and 32.
	S. 89° 31' W., on the E. and W. center line of sec. 31.
	Ascend NE. slope, through heavy timber and dense undergrowth.
2.80	Spur, slopes N. 40° W.; desc. NW. slope.
11.10	Creek, 1 lk. wide, course N. 15° E.; asc. NE. slope.
19.70	Spur, slopes N. 40° W.; desc. NW. slope.
27.50	Creek, 2 lks. wide, course N. 25° E.; asc. SE. slope.
42.65	Spur, slopes N. 40° W.; desc. broken SW. slope.
66.40	Creek, 5 lks. wide, course N. 10° E.; asc. NE. slope, changing to SE.
80.54	The 1/4 sec. cor. of secs. 31 and 36, on the W. bdy. of the Tp., perpetuated and recorded by James W. Byron, Deputy Douglas County Surveyor, in 1956, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.
	<p>COUNTY SURVEYORS OFFICE</p> <p style="margin-left: 40px;">T 23 S</p> <p style="margin-left: 40px;">R 8 W R 7 W</p> <p style="margin-left: 40px;">1/4 S 36 S 31</p> <p style="margin-left: 40px;">1956</p>
	from which the remains of the original bearing trees
	A fir stub, 16 ins. diam., bears S. 60° E., 25 lks. dist., with scribe marks BT visible on an opened blaze.
	A rootcrown, bears West, 11 lks. dist., with a down fir alongside, 20 ins. diam., no marks visible.
	and bearing trees mkd. by Byron
	A fir, 10 ins. diam., bears S. 51° E., 25 1/2 lks. dist., with scribe marks 31 visible on a partially healed blaze.
	A fir, 19 ins. diam., bears N. 32° W., 27 lks. dist., with a healed blaze.
	and a tree not of known record
	A fir, 15 ins. diam., bears N. 38 1/2° W., 25 1/2 lks. dist., with a healed blaze.
	and a new bearing tree
	A fir, 12 ins. diam., bears S. 63 1/4° E., 17 lks. dist., mkd. 1/4 S31 BT.