

County Surveyor's Record, Douglas County, Oregon

17607

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 21 S., R. 4 W., Willamette Meridian, Oregon

CHAINS

Set a 5 ft. steel fence post alongside iron rod.

Corner is located in rock quarry where it is impracticable to establish a standard monument.

Descend over W. slope.

49.44

Point for a witness point, on line bet. secs. 14 and 23.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

WP
S 14
S 23
1982

from which

A white fir, 13 ins. diam., bears S. 15° W.,
133 1/2 lks. dist., mkd. X BT.

No other suitable trees available.

Point is located at corner of rock quarry, edge bears N. 85° W. and S., quarry area to the N. and E.

Descend over W. slope, through scattering timber and moderate undergrowth.

61.13

An unrecorded point, established by the Oregon State Highway Department, monumented with an iron rod, 5/8 in. diam., firmly set, projecting 1 in. above ground, also bottom of descent, slopes S.; asc. over SE. slope.

67.40

Dirt road, 15 lks. wide, bears N. 25° E. and S. 25° W.

79.78

The cor. of secs. 14, 15, 22, and 23, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.

FD OK 10/90 M110-72 T 21 S R 4 W
 S 15 | S 14
 S 22 | S 23
 1980

from which the remains of a bearing tree of unknown origin, recorded by Jelley and Rogers

A decayed fir stump, 34 ins. diam., bears S. 52° E.,
16 lks. dist., with scribe marks 21 R4W T visible
on opened blaze.

and bearing trees mkd. by Jelley and Rogers

A fir, 16 ins. diam., bears N. 54 1/2° E., 11 lks.
dist., with scribe marks T21S R4W S14 BT visible
on open blaze.

A fir, 6 ins. diam., bears S. 22 1/4° E., 92 lks.
dist., with scribe marks T21S R4W S23 BT visible
on open blaze.

A fir, 10 ins. diam., bears S. 29° W., 25 lks.
dist., with scribe marks T21S R4W S22 BT visible
on open blaze.