

# County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of Part of North Boundary of **17612**  
T. 32 S., R. 1 E.

**CHAINS**

Set an iron post, 3 ft. long, 2 ins. diam., 17 ins. in the ground to bedrock, and in a mound of stone to top, for cor. of secs. 3 and 4 only, with brass cap mkd.

T 31 S    R 1 E  
    S 34  
-----  
    S 4 | S 3  
T 32 S | R 1 E  
    1936

from which

A fir, 20 ins. diam., bears S. 47° E., 9 lks. dist.,  
mkd. T 32 S R 1 E S 3 B T. (Old B.T.)

A fir, 17 ins. diam., bears S. 30° W., 48 lks. dist.,  
mkd. T 32 S R 1 E S 4 B T. (New B.T.)

Land, mountainous.  
Soil, stony; 4th rate.  
Timber, fir, yellow pine, and white oak.  
Undergrowth, manzanita, spirea, vinemaple, and poison oak.

N. 89° 23' E., along N. bdy. of sec. 3.

Desc. 380 ft. over E. slope, through scattering timber and light undergrowth.

10.20 Elkhorn Creek, 15 lks. wide, course SE.; asc. 280 ft. over SW. slope; enter heavy timber and dense undergrowth, bears NW. and SE.

23.75 Small spur, slopes S.; asc. 315 ft. over S. slope, changing to W. slope.

34.93 A point 40.00 chs, in departure from the cor. of secs. 33 and 34, previously described.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for 1/4 sec. cor. of sec. 34 only, with brass cap mkd.

1/4 S 34  
1936

from which

An oak, 13 ins. diam., bears N. 72° E., 30 lks. dist.,  
mkd. 1/4 S 34 B T.

A sugar pine, 28 ins. diam., bears N. 49° W., 86 lks. dist.,  
mkd. 1/4 S 34 B T.

Spur, slopes S. 10° W.; desc. 45 ft. over SE. slope.

37.25 Draw, drains S. 10° E.; along S. slope.

37.89 Point for old 1/4 sec. cor. of secs. 3 and 34, determined by reference to the record bearing and distance to the original NW. bearing tree. Hereafter this cor. will refer to sec. 3 only.

At point for cor.,

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for 1/4 sec. cor. of sec. 3 only, with brass cap mkd.

1/4 S 3  
1936

from which