

# County Surveyor's Record, Douglas County, Oregon

17613

Dependent Resurvey of Part of North Boundary of  
T. 32 S., R. 1 E.

CHAINS

A fir, 60 ins. diam., bears N. 58° W., 18 lks. dist.,  
mkd. on bark 1/4 S B T. I obliterate the marks.  
(Old B.T.)

A pine, 38 ins. diam., bears S. 83° E., 58 lks. dist.,  
mkd. 1/4 S 3 B T. (New B.T.)

A fir, 15 ins. diam., bears S. 41° W., 73 lks. dist.,  
mkd. 1/4 S 3 B T. (New B.T.)

Thence

N. 89° 09' E., continuing measurements.

Asc. 155 ft. over SW. slope.

44.85 Ridge, bears NW. and S. 30° E.; desc. 730 ft. over E. slope;  
enter scattering timber, bears NW. and S. 30° E.

64.55 Spring branch, 1 lk. wide, course N. 10° E.; asc. 10 ft.  
over NW. slope.

67.10 Spur, slopes N. 30° E.; desc. 130 ft. over NE. slope, chang-  
ing to E. slope.

73.30 Sugar Pine Creek, 15 lks. wide, course SE.; asc. 15 ft.  
over SW. slope.

74.93 A point 80.00 chs. in departure from the cor. of secs. 33  
and 34, previously described.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the  
ground, for cor. of secs. 34 and 35 only, with brass cap  
mkd.

T 31 S	R 1 E
S 34	S 35
T 32 S R 1 E	
S 3	

1936

from which

A fir, 12 ins. diam., bears N. 10° E., 42 lks. dist.,  
mkd. T 31 S R 1 E S 35 B T.

A fir, 7 ins. diam., bears N. 52° W., 39 lks. dist.,  
mkd. T 31 S R 1 E S 34 B T.

Over level land.

75.61 The original cor. of secs. 2, 3, 34, and 35, which is a  
basalt stone, 12 x 6 x 6 ins., firmly set, mkd. with 2  
notches on E. and 4 notches on W. edge. Hereafter this  
cor. will refer to secs. 2 and 3 only.

At point for cor.,

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in  
the ground, for cor. of secs. 2 and 3 only, with brass  
cap mkd.

T 31 S	R 1 E
S 35	
S 3 S 2	
T 32 S R 1 E	
1936	

from which

A fir, 20 ins. diam., bears S. 61° W., 6 lks. dist.,  
evidence of ax marks visible. (Old B.T.)