

# County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of Part of North Boundary of **17614**  
T. 32 S., R. 1 E.

**CHAINS**

A fir, 10 ins. diam., bears S. 26° E., 94 lks. dist.,  
mkd. T 32 S R 1 E S 2 B T. (New B.T.)

A yew, 12 ins. diam., bears S. 46° W., 55 lks. dist.,  
mkd. T 32 S R 1 E S 3 B T. (New B.T.)

Land, mountainous.

Soil, stony; 4th rate.

Timber, fir, yew, chinquapin, oak, pine, cedar, and  
madrona.

Undergrowth, vinemaple, hazel, poison oak, slickleaf,  
Oregon grape, manzanita, dogwood, and bracken.

N. 89° 09' E., along N. bdy. of sec. 2.

Over level land, through heavy timber and dense under-  
growth.

2.25 Creek, 4 lks. wide, course S. 15° W.; asc. 440 ft. over W.  
slope.

2.80 Trail and Forest Service Telephone line, bears N. 15° W. and  
S. 15° E.

21.35 Spur, slopes S. 25° W.; along S. slope.

23.35 Small draw, drains S.; asc. 60 ft. over SW. slope.

29.30 Head of draw, drains S. 15° W.; asc. 320 ft. over SW. slope.

37.40 Ridge, bears N. 10° W. and S. 10° E.; leave dense and enter  
light undergrowth, bears N. and S.; over gradual S.  
slope.

39.32 A point 40.00 chs. in departure from the cor. of secs. 34  
and 35, previously described.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the  
ground, for 1/4 sec. cor. of sec. 35 only, with brass cap  
mkd.

1/4 S 35

1936

from which

An oak, 28 ins. diam., bears N. 15° E., 87 lks. dist.,  
mkd. 1/4 S 35 B T.

A fir, 30 ins. diam., bears N. 40° W., 83 lks. dist.,  
mkd. 1/4 S 35 B T.

Desc. 5 ft. over E. slope.

39.70 Point for the old 1/4 sec. cor. of secs. 2 and 35, as  
determined by reference to the record distance to the  
original bearing trees. Hereafter this cor. will refer  
to sec. 2 only.

At point for cor.,

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the  
ground, for 1/4 sec. cor. of sec. 2 only, with brass cap  
mkd.

1/4 S 2

1936

from which

A fir, 25 ins. diam., bears N. 35° W., 68 lks. dist.,