

County Surveyor's Record, Douglas County, Oregon

17615

Dependent Resurvey of Part of North Boundary of
T. 32 S., R. 1 E.

CHAINS

mkd. 1/4 S B T. I obliterate the marks. (Old B.T.)

An oak, 20 ins. diam., bears S. 58° E., 51 lks. dist., blaze healed; I do not open. I reblaze and re-mark this tree 1/4 S 2 B T. (Old B.T.)

A fir, 32 ins. diam., bears S. 21° W., 48 lks. dist., mkd. 1/4 S 2 B T. (New B.T.)

Thence

N. 89° 04' E., continuing measurements.

Desc. 130 ft. over E. slope.

46.90 Head of draw, drains S. 70° E.; desc. 185 ft. over SE. slope.

53.20 Trail, from Abbot Prairie to Sugar Pine Creek, bears N. 15° E. and S. 15° W.

58.10 Draw, drains S. 10° E.; asc. 170 ft. over SW. slope.

63.85 Spur, slopes S. 15° E.; desc. 135 ft. over SE. slope.

67.75 Enter opening, bears NE. and SE.

73.10 Draw, drains S. 15° W.; asc. 90 ft. over SW. slope.

76.80 Trail, from Bitter Lick Creek to Butler Butte, bears N. and S.

77.50 Enter heavy timber and light undergrowth, bears N. and S.

79.32 The cor. of secs. 1, 2, 35, and 36, which is a basalt stone, 16 x 12 x 7 ins., firmly set, mkd. with 1 notch on E. and 5 notches on W. edge.

At point for cor.,

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of secs. 1, 2, 35, and 36, with brass cap mkd.

T 31 S	R 1 E
S 35	S 36
S 2	S 1
T 32 S	
1936	

from which

A white oak, 18 ins. diam., bears N. 46° E., 73 lks. dist., scribe marks illegible. (Old B.T.)

A fir, 7 ins. diam., bears N. 63° E., 29 lks. dist., mkd. T 31 S R 1 E S 36 B T. (New B.T.)

A fir, 12 ins. diam., bears S. 18° E., 24 lks. dist., mkd. T 32 S R 1 E S 1 B T. (New B.T.)

A fir, 10 ins. diam., bears S. 48° W., 40 lks. dist., mkd. T 32 S R 1 E S 2 B T. (New B.T.)

A fir, 10 ins. diam., bears N. 29° W., 49 lks. dist., mkd. T 31 S R 1 E S 35 B T. (New B.T.)

Land, mountainous.
Soil, coarse sandy loam and stony; 3rd and 4th rate.
Timber, fir, pine, chinquapin, oak, yew, cedar, hemlock, and madrona.
Undergrowth, vinemapple, slickleaf, manzanita, hazel, scrub