

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of Part of North Boundary of 17616
T. 32 S., R. 1 E.

CHAINS

oak, Oregon grape, and bracken.

N. 88° 50' E., bet. secs. 1 and 36.

Asc. 115 ft. over SW. slope, through heavy timber and light undergrowth.

9.85 Spur, slopes S. 10° W.; desc. 15 ft. over SE. slope.

13.45 Small draw, drains S.; asc. 5 ft. over SW. slope.

14.80 Small spur, slopes S.; desc. 180 ft. over SE. slope.

24.40 Spur, slopes SE.; desc. 395 ft. over NE. slope, changing to E. slope.

38.55 Bitter Lick Creek, 20 lks. wide, course S. 15° E.; asc. 6 ft. over gradual SW. slope.

39.70 Bitter Lick Creek Way Trail, bears N. and S.

40.01 The 1/4 sec. cor. of secs. 1 and 36, which is a basalt stone, 18 x 9 x 9 ins., firmly set, with no marks legible.

At point for cor.,

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for 1/4 sec. cor., with brass cap mkd.

1/4 $\frac{S \ 36}{S \ 1}$

1936

from which

A white fir, 20 ins. diam., bears N. 5° W., 29 lks. dist., blaze healed; I do not open. I reblaze and re-mark this tree 1/4 S 36 B T. (Old B.T.)

A yew, 12 ins. diam., bears S. 55° E., 9 lks. dist., mkd. 1/4 S B T. I re-mark this tree 1/4 S 1 B T. (Old B.T.)

Thence

N. 89° 13' E., continuing measurements.

Asc. 95 ft. over SW. slope.

44.55 Spur, slopes S.; desc. 10 ft. over S. slope.

49.40 Creek, 1 lk. wide, course S. 60° W.; asc. 500 ft. over NW. slope.

68.40 Small spur, slopes N.; desc. 20 ft. over NE. slope.

70.40 Draw, drains NW.; asc. 150 ft. over W. slope.

80.22 Point for the cor. of Tps. 31 and 32 S., Rs. 1 and 2 E., as determined by the intersection of old fence lines. This point agrees approximately with the theoretical position and is locally accepted.

At point for cor.,

Set an iron post, 3 ft. long, 3 ins. diam., 27 ins. in the ground, for cor. of Tps. 31 and 32 S., Rs. 1 and 2 E., with brass cap mkd.