

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of Part of North Boundary of 17618
T. 32 S., R. 1 E.

CHAINS

80.34

Fall 59 lks. W. of cor. of secs. 7, 12, 13, and 18.

From the cor. of secs. 7, 12, 13, and 18.

North, bet. secs. 7 and 12.

39.93

Fall 11 lks. E. of 1/4 sec. cor.

79.92

Fall 69 lks. E. of cor. of secs. 1, 6, 7, and 12.

From the cor. of secs. 1, 6, 7, and 12.

North, bet. secs. 1 and 6.

40.00

Fall 84 lks. E. of 1/4 sec. cor.

79.96

Fall 132 lks. E. of cor. of Tps. 30 and 31 S., Rs. 1 and 2 E.

True Line

From the cor. of Tps. 31 and 32 S., Rs. 1 and 2 E.,
previously described.

N. 0° 03' E., along W. bdy. of sec. 31.

Asc. 135 ft. over gradual SW. slope, through heavy timber
and light undergrowth.

22.85

Spring, drains SW.; asc. 35 ft. over SW. slope.

27.40

Spur, slopes NW.; desc. 15 ft. over NW. slope.

32.06

(35.75 chs. minus the northing of the fractional S. bdy.
of Tp. counted from the West.)

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the
ground, for 1/4 sec. cor. of sec. 36 only, with brass cap
mkd.

1/4 S 36
|
1936

from which

A pine, 32 ins. diam., bears S. 70° W., 69 lks. dist.,
mkd. 1/4 S 36 B T.

A fir, 12 ins. diam., bears N. 19° W., 24 lks. dist.,
mkd. 1/4 S 36 B T.

Desc. 30 ft. over NW. slope.

35.45

Spur, slopes N. 30° E.; desc. 100 ft. over NE. slope.

40.35

The old 1/4 sec. cor. of secs. 31 and 36, which is a granite
stone, 12 x 9 x 9 ins., firmly set, mkd. with a cross (X)
on top.

I change this cor. to refer to sec. 31 only.

At point for cor.,

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the
ground, for 1/4 sec. cor. of sec. 31 only, with brass cap
mkd.

|
1/4 S 31
1936

from which

A white fir, 17 ins. diam., bears N. 4° E., 41 lks.
dist., blaze healed; I do not open. I reblaze and
re-mark this tree 1/4 S 31 B T. (Old B.T.)