

County Surveyor's Record, Douglas County, Oregon

17619

Dependent Resurvey of W. Bdy. of T. 31 S., R. 2 E.

CHAINS

A cedar, 20 ins. diam., bears S. 85 1/2° W., 36 lks. dist., mkd. 1/4 S B T. I obliterate the marks. (Old B.T.)

A fir, 25 ins. diam., bears S. 57° E., 154 lks. dist., mkd. 1/4 S 31 B T. (New B.T.)

Thence

N. 0° 12' W., continuing measurements.

40.38 Dry creek bed, 3 lks. wide, course N. 70° W.; asc. 35 ft. over SW. slope.

43.90 Spur, slopes W.; desc. 45 ft. over NW. slope.

47.10 Draw, drains S. 80° W.; asc. 200 ft. over SW. slope.

57.10 Spur, slopes N. 80° W.; desc. 205 ft. over N. slope, changing to NE. slope.

63.90 Draw, drains N. 60° W.; asc. 30 ft. over N. slope.

66.80 Spur, slopes NW.; desc. 185 ft. over N. slope.

72.06 Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of secs. 25 and 36 only, with brass cap mkd.

T 31 S	T 31 S
S 25	R 2 E
S 36	S 31
R 1 E	
1936	

from which

A yew, 7 ins. diam., bears S. 61° W., 74 lks. dist., mkd. T 31 S R 1 E S 36 B T.

A yew, 12 ins. diam., bears N. 52° W., 83 lks. dist., mkd. T 31 S R 1 E S 25 B T.

Desc. 35 ft. over N. slope.

77.00 Spring branch, 1 lk. wide, course W.; asc. 110 ft. over SW. slope.

80.09 The old cor. of secs. 25, 30, 31, and 36, which is a badly decomposed sandstone, 8 x 6 x 5 ins., firmly set.

I change this cor. to refer to secs. 30 and 31 only.

At point for cor.,

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of secs. 30 and 31 only, with brass cap mkd.

T 31 S	T 31 S
R 1 E	S 30
	S 31
S 25	R 2 E
1936	

from which

A madrona, 7 ins. diam., bears N. 18° E., 32 lks. dist., blaze partially healed; scribe marks 31 S R 2 E visible. (Old B.T.)

A white fir, 15 ins. diam., bears S. 25 3/4° E., 28 lks. dist., blaze healed; I do not open. I reblaze and