

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of W. Bdy. of T. 31 S., R. 2 E. 17620

CHAINS

re-mark this tree T 31 S R 2 E S 31 B T. (Old B.T.)

A fir, 20 ins. diam., bears S. 8° W., 34 lks. dist., mkd. T 31 S R 1 E S 36 B T. I obliterate the marks. (Old B.T.)

A madrona, 7 ins. diam., bears N. 47° W., 52 lks. dist., scribe marks effaced by decay. (Old B.T.)

A sugar pine, 25 ins. diam., bears N. 12° E., 91 lks. dist., mkd. T 31 S R 2 E S 30 B T. (New B.T.)

Land, mountainous.
Soil, sandy loam; 2nd and 3rd rate.
Timber, fir, pine, madrona, chinquapin, oak, and cedar.
Undergrowth, vinemaple, hazel, spirea, Oregon grape, and bracken.

N. 0° 10' W., along W. bdy. of sec. 30.

Asc. 135 ft. over SW. slope, through heavy timber and light undergrowth.

9.10 Spur, slopes N.; desc. 35 ft. over NW. slope.

12.55 Draw, drains SW.; asc. 35 ft. over S. slope.

14.25 Spur, slopes S. 80° W.; desc. 180 ft. over N. slope.

22.65 Draw, drains W.; asc. 45 ft. along W. slope.

28.60 Draw, drains S. 25° W.; asc. 35 ft. over SE. slope.

31.97 A point 40.00 chs. in latitude from the cor. of secs. 25 and 36.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for 1/4 sec. cor. of sec. 25 only, with brass cap mkd.

1/4 S 25
|
1936

from which

A fir, 8 ins. diam., bears S. 43° W., 111 lks. dist., mkd. 1/4 S 25 B T.

A fir, 22 ins. diam., bears N. 77° W., 64 lks. dist., mkd. 1/4 S 25 B T.

Asc. 155 ft. over SW. slope.

37.10 Spur, slopes W.; desc. 10 ft. along W. slope.

39.76 The old 1/4 sec. cor. of secs. 25 and 30, which is a sandstone, 12 x 9 x 4 ins., firmly set, mkd. 1/4 on W. face.

I change this cor. to refer to sec. 30 only.

At point for cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for 1/4 sec. cor. of sec. 30 only, with brass cap mkd.

1/4 S 30
|
1936