

County Surveyor's Record, Douglas County, Oregon

17621

Dependent Resurvey of W. Bdy. of T. 31 S., R. 2 E.

CHAINS

from which

A fir, 8 ins. diam., bears S. 69° E., 11 lks. dist., blaze healed; I do not open. I reblaze and re-mark this tree 1/4 S 30 B T. (Old B.T.)

A fir, 22 ins. diam., bears N. 69° W., 13 lks. dist., mkd. 1/4 S B T. I obliterate the marks. (Old B.T.)

A fir, 18 ins. diam., bears N. 33° E., 41 lks. dist., mkd. 1/4 S 30 B T. (New B.T.)

Thence

N. 0° 07' E., continuing measurements.

Asc. 75 ft. over SW. slope.

47.65 Spur, slopes S. 70° W.; asc. 145 ft. along W. slope, changing to SW. slope.

61.40 Spur, slopes W.; desc. 110 ft. over NW. slope.

66.40 Draw, drains W.; asc. 25 ft. over SW. slope.

68.40 Spur, slopes W.; asc. 8 ft. along W. slope.

71.97 A point 80.00 chs. in latitude from the cor. of secs. 25 and 36.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of secs. 24 and 25 only, with brass cap mkd.

T 31 S	T 31 S	
	S 24	
	S 25	R 2 E
R 1 E		S 30
1936		

from which

A fir, 6 ins. diam., bears S. 31° W., 74 lks. dist., mkd. T 31 S R 1 E S 25 B T.

A fir, 18 ins. diam., bears N. 13 1/2° W., 73 lks. dist., mkd. T 31 S R 1 E S 24 B T.

Desc. 105 ft. along W. slope, changing to N. slope.

79.93 The old cor. of secs. 19, 24, 25, and 30, which is a basalt stone, 12 x 9 x 9 ins., firmly set, mkd. with a cross (X) on top, and 2 notches on S. edge.

I change this cor. to refer to secs. 19 and 30 only.

At point for cor.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of secs. 19 and 30, only, with brass cap mkd.

T 31 S	T 31 S	
	S 19	
R 1 E	S 30	
		R 2 E
1936		

from which

A fir stump, 14 ins. diam., bears N. 67° E., 31 lks. dist., scribe marks effaced by fire. (Old B.T.)