

# County Surveyor's Record, Douglas County, Oregon

17622

Dependent Resurvey of W. Bdy. of T. 31 S., R. 2 E.

**CHAINS**

A fir, 33 ins. diam., bears S. 52° E., 28 lks. dist., blaze healed; I do not open. I reblaze and re-mark this tree T 31 S R 2 E S 30 B T. (Old B.T.)

A fir stump, 24 ins. diam., bears S. 25° W., 16 lks. dist., scribe marks effaced by fire. (Old B.T.)

A fir stump, 10 ins. diam., bears N. 77° W., 16 lks. dist., scribe marks effaced by decay. (Old B.T.)

A fir, 25 ins. diam., bears N. 53° E., 66 lks. dist., mkd. T 31 S R 2 E S 19 B T. (New B.T.)

Land, mountainous.

Soil, sandy loam; 2nd and 3rd rate.

Timber, fir, pine, madrona, oak, chinquapin, and yew.

Undergrowth, vinemaple, hazel, Oregon grape, slickleaf, and bracken.

N. 0° 12' W., along W. bdy. of sec. 19.

Desc. 75 ft. over N. slope, through heavy timber and light undergrowth.

3.75

Draw, drains W.; asc. 185 ft. over rocky SW. slope, changing to S. slope.

9.60

Spur, slopes W.; desc. 350 ft. over NW. slope, changing to W. slope.

32.04

A point 40.00 chs. in latitude from the cor. of secs. 24 and 25.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for 1/4 sec. cor. of sec. 24 only, with brass cap mkd.

1/4 S 24  
1936

from which

A white fir, 8 ins. diam., bears N. 9° W., 18 lks. dist., mkd. 1/4 S 24 B T.

A fir, 45 ins. diam., bears S. 63° W., 13 lks. dist., mkd. 1/4 S 24 B T.

Asc. 20 ft. over SW. slope.

33.00

Point of small spur, slopes S. 60° W.; desc. 7 ft. over NW. slope.

33.50

Creek, 3 lks. wide, course S. 60° W.; asc. 20 ft. over S. slope.

34.20

Point of spur, slopes W.; desc. 30 ft. over NW. slope.

36.80

Bitter Lick Creek, 20 lks. wide, course S. 75° W.; asc. 75 ft. over S. slope.

37.65

Bitter Lick Creek Way Trail, bears N. 80° E. and S. 80° W.

39.75

The old 1/4 sec. cor. of secs. 19 and 24, which is a basalt stone, 10 x 8 x 8 ins., firmly set.

I change this cor. to refer to sec. 19 only.

At point for cor.,