

County Surveyor's Record, Douglas County, Oregon

17623

Dependent Resurvey of W. Bdy. of T. 31 S., R. 2 E.

CHAINS													
	<p>Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for 1/4 sec. cor. of sec. 19 only, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">1/4 S 19</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">1936</td> </tr> </table> </div> <p style="text-align: right; margin-right: 100px;">from which</p> <p>A cedar, 7 ins. diam., bears N. 19° E., 12 lks. dist., mkd. 1/4 S B T. (Old B.T.)</p> <p>A fir snag, 26 ins. diam., bears S. 47° W., 28 lks. dist., scribe marks effaced by decay. (Old B.T.)</p> <p>A fir, 40 ins. diam., bears N. 69° E., 34 lks. dist., mkd. 1/4 S 19 B T. (New B.T.)</p> <p>A fir, 25 ins. diam., bears S. 58° E., 58 lks. dist., mkd. 1/4 S 19 B T. (New B.T.)</p> <p>Spur, slopes SE.</p> <p>Thence</p> <p>N. 0° 07' W., continuing measurements.</p> <p>Asc. 70 ft. over SE. slope.</p>	1/4 S 19	1936										
1/4 S 19													
1936													
43.60	<p>Draw, drains S. 70° E.; asc. 640 ft. over rocky S. slope. changing to SE. slope.</p>												
62.65	<p>Spur, slopes S. 75° E.; desc. 40 ft. over NE. slope.</p>												
65.60	<p>Draw, drains S. 80° E.; asc. 180 ft. over SE. slope.</p>												
70.25	<p>Spur, slopes S. 80° E.; desc. 35 ft. over NE. slope.</p>												
72.04	<p>A point 80.00 chs. in latitude from the cor. of secs. 24 and 25.</p> <p>Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of secs. 13 and 24 only, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">T 31 S</td> <td style="padding: 0 5px;"> </td> <td style="padding: 0 5px;">T 31 S</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 13</td> <td style="padding: 0 5px;"> </td> <td style="padding: 0 5px;">R 2 E</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 24</td> <td style="padding: 0 5px;"> </td> <td style="padding: 0 5px;">S 19</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">R 1 E</td> <td style="padding: 0 5px;"> </td> <td style="padding: 0 5px;">1936</td> </tr> </table> </div> <p style="text-align: right; margin-right: 100px;">from which</p> <p>A fir, 30 ins. diam., bears S. 12° W., 85 lks. dist., mkd. T 31 S R 1 E S 24 B T.</p> <p>A fir, 12 ins. diam., bears N. 38° W., 30 lks. dist., mkd. T 31 S R 1 E S 13 B T.</p> <p>Desc. 30 ft. over NE. slope.</p>	T 31 S		T 31 S	S 13		R 2 E	S 24		S 19	R 1 E		1936
T 31 S		T 31 S											
S 13		R 2 E											
S 24		S 19											
R 1 E		1936											
73.75	<p>Draw, drains E.; asc. 130 ft. over SE. slope.</p>												
79.41	<p>Point for the old cor. of secs. 13, 18, 19, and 24, as determined by reference to the record bearing and distance to the original NW. bearing tree.</p> <p>I change this cor. to refer to secs. 18 and 19 only.</p> <p>At point for cor.,</p>												