

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of W. Bdy. of T. 31 S., R. 2 E. 17624

CHAINS

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of secs. 18 and 19 only, with brass cap mkd.

T 31 S	T 31 S
R 1 E	S 18
S 13	S 19
	R 2 E
	1936

from which

A white fir, 27 ins. diam., bears N. 72° W., 15 lks. dist., mkd. beneath the correct overgrowth for date of original survey, T 31 S R 1 E S 13 B T. I obliterate the marks. (Old B.T.)

A fir, 18 ins. diam., bears N. 60° E., 38 lks. dist., mkd. T 31 S R 2 E S 18 B T. (New B.T.)

A fir, 12 ins. diam., bears S. 35° E., 37 lks. dist., mkd. T 31 S R 2 E S 19 B T. (New B.T.)

Land, mountainous.

Soil, sandy loam and rocky; 3rd and 4th rate.

Timber, fir, oak, pine, madrona, yew, chinquapin, and alder.

Undergrowth, vinemaple, slickleaf, spirea, Oregon grape, poison oak, hazel, and bracken.

N. 0° 25' E., along W. bdy. of sec. 18.

Asc. 70 ft. over SE. slope, through heavy timber and light undergrowth.

3.25 Spur, slopes E.; desc. 90 ft. over broken NE. slope.

19.50 Spur, slopes N. 80° E.; desc. 380 ft. over NE. slope.

26.20 Bluff, 30 ft. high, bears E. and W.

28.90 Creek, 3 lks. wide, course N. 85° E.; asc. 50 ft. over SE. slope.

30.45 Spur, slopes S. 80° E.; desc. 70 ft. over NE. slope.

32.63 A point 40.00 chs. in latitude from the cor. of secs. 13 and 24.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for 1/4 sec. cor. of sec. 13 only, with brass cap mkd.

1/4 S 13	
	1936

from which

A fir, 28 ins. diam., bears S. 42° W., 160 lks. dist., mkd. 1/4 S 13 B T.

A fir, 22 ins. diam., bears N. 72° W., 29 lks. dist., mkd. 1/4 S 13 B T.

Desc. 25 ft. over NE. slope.

34.65 Creek, 12 lks. wide, course S. 15° E.; asc. 200 ft. over SW. slope; leave heavy and enter scattering timber, bears N. 15° W. and S. 15° E.

40.17 Proportionate measurement,