

County Surveyor's Record, Douglas County, Oregon

17625

Dependent Resurvey of W. Bdy. of T. 31 S., R. 2 E.

CHAINS

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for 1/4 sec. cor. of sec. 18 only, with brass cap mkd.

1/4 S 18
1936

from which

A fir, 12 ins. diam., bears N. 44° E., 19 lks. dist., mkd. 1/4 S 18 B T.

A fir, 12 ins. diam., bears S. 6° E., 27 lks. dist., mkd. 1/4 S 18 B T.

Asc. 160 ft. over gradual SW. slope, changing to S. slope.

59.50 Spur, slopes W.; desc. 120 ft. over NW. slope.

66.35 Creek, 10 lks. wide, course S. 25° W.; asc. 110 ft. over SE. slope. Leave scattering and enter heavy timber, bears N. 25° E. and S. 25° W.

72.63 A point 80.00 chs. in latitude from the cor. of secs. 13 and 24.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of secs. 12 and 13 only, with brass cap mkd.

T 31 S	T 31 S
S 12	R 2 E
S 13	S 18
R 1 E	1936

from which

A white fir, 25 ins. diam., bears S. 46 1/2° W., 51 lks. dist., mkd. T 31 S R 1 E S 13 B T.

A fir, 42 ins. diam., bears N. 13° W., 62 lks. dist., mkd. T 31 S R 1 E S 12 B T.

Asc. 170 ft. over SE. slope.

80.34 The old cor. of secs. 7, 12, 13, and 18, which is a lava stone, 16 x 12 x 12 ins., firmly set.

I change this cor. to refer to secs. 7 and 18 only.

At point for cor.,

Set an iron post, 3 ft. long, 2 ins. diam., 20 ins. in the ground to bedrock, and in a mound of stone to top, for cor. of secs. 7 and 18 only, with brass cap mkd.

T 31 S	T 31 S
R 1 E	S 7
S 12	S 18
S 12	R 2 E
S 12	1936

from which

A fir, 40 ins. diam., bears N. 56° E., 23 lks. dist., blaze healed; I do not open. I reblaze and re-mark this tree T 31 S R 2 E S 7 B T. (Old B.T.)

A fir snag, 30 ins. diam., bears S. 50° W., 124 lks. dist., mkd. T 31 S R 1 E S 13. I obliterate the marks. (Old B.T.)