

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of W. Bdy. of T. 31 S., R: 2 E. **17626**

CHAINS

A fir snag, 40 ins. diam., bears N. 66° W., 83 lks. dist., mkd. T 31 S R 1 E S 12 B T. I obliterate the marks. (Old B.T.)

A pine, 6 ins. diam., bears S. 75 1/2° E., 133 lks. dist., mkd. T 31 S R 2 E S 18 B T. (New B.T.)

Land, mountainous.
Soil, sandy loam and rocky; 2nd, 3rd, and 4th rate.
Timber, fir, pine, madrona, chinquapin, oak, maple, yew, and cedar.
Undergrowth, vinemaple, slickleaf, rhododendron, Oregon grape, dogwood, poison oak, and bracken.

N. 0° 09' W., along W. bdy. of sec. 7.

Asc. 510 ft. over SE. slope, through scattering timber and dense undergrowth.

29.00 Spur, slopes S. 50° E.; desc. 25 ft. over NE. slope.

30.70 Draw, drains S. 60° E.; asc. 50 ft. over SE. slope.

32.29 A point 40.00 chs. in latitude from the cor. of secs. 12 and 13.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for 1/4 sec. cor. of sec. 12 only, with brass cap mkd.

1/4 S 12
|
1936

from which

A fir, 27 ins. diam., bears S. 53° W., 69 lks. dist., mkd. 1/4 S 12 B T.

A fir, 5 ins. diam., bears N. 16° W., 49 lks. dist., mkd. 1/4 S 12 B T.

Asc. 125 ft. over SE. slope.

39.93 The old 1/4 sec. cor. of secs. 7 and 12, which is a basalt stone, 15 x 10 x 6 ins., loosely set, mkd. 1/4 on W. face.

I change this cor. to refer to sec. 7 only.

At point for cor.,

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for 1/4 sec. cor. of sec. 7 only, with brass cap mkd.

| 1/4 S 7
1936

from which

A white fir, 30 ins. diam., bears N. 73° E., 14 lks. dist., blaze healed; I do not open. (Old B.T.)

A cedar, 12 ins. diam., bears N. 45° W., 8 lks. dist., mkd. 1/4 S B T. I obliterate the marks. (Old B.T.)

A cedar, 22 ins. diam., bears N. 32° E., 81 lks. dist., mkd. 1/4 S 7 B T. (New B.T.)

A white fir, 35 ins. diam., bears S. 47° E., 71 lks.