

County Surveyor's Record, Douglas County, Oregon

17627

Dependent Resurvey of W. Bdy. of T. 31 S., R. 2 E.

CHAINS

dist., mkd. 1/4 S 7 B T. (New B.T.)

Thence

N. 0° 50' W., continuing measurements.

Asc. 650 ft. over SE. slope.

65.00 Enter heavy timber and light undergrowth, bears E. and W.

72.29 A point 80.00 chs. in latitude from the cor. of secs. 12 and 13.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of secs. 1 and 12, with brass cap mkd.

T 31 S	T 31 S
S 1	R 2 E
S 12	S 7
R 1 E	1936

from which

A cedar, 25 ins. diam., bears S. 39° W., 84 lks. dist., mkd. T 31 S R 1 E S 12 B T.

A cedar, 35 ins. diam., bears N. 13° W., 16 lks. dist., mkd. T 31 S R 1 E S 1 B T.

Asc. 30 ft. over SE. slope.

75.60 Forest Service road, bears N. 60° E. and S. 60° W.; Forest Service telephone line parallels the road.

77.10 Divide bet. Rogue River and South Umpqua River, bears E. and W.; desc. 30 ft. over NE. slope.

79.92 The old cor. of secs. 1, 6, 7, and 12, which is a porphyry stone, 18 x 12 x 9 ins., firmly set.

I change this cor. to refer to secs. 6 and 7 only.

At point for cor.,

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of secs. 6 and 7, with brass cap mkd.

T 31 S	T 31 S
R 1 E	S 6
S 1	S 7
R 2 E	1936

from which

A white fir, 50 ins. diam., bears N. 46° E., 188 lks. dist., blaze healed; I do not open. I reblaze and re-mark this tree T 31 S R 2 E S 6 B T. (Old B.T.)

A white fir, 22 ins. diam., bears S. 59° E., 49 lks. dist., scribe marks S 7 recently uncovered. (Old B.T.)

A white fir, 50 ins. diam., bears S. 23° W., 41 lks. dist., mkd. T 31 S R 1 E S 12 B T. I obliterate the marks. (Old B.T.)

A white fir, 42 ins. diam., bears S. 35° E., 76 lks. dist., mkd. T 31 S R 2 E S 7 B T. (New B.T.)