

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of W. Bdy. of T. 31 S., R. 2 E. 17628

CHAINS

Land, mountainous.
Soil, sandy loam and rocky; 3rd and 4th rate.
Timber, fir, pine, madrona, chinquapin, oak, yew, and cedar.
Undergrowth, vinemaple, slickleaf, Oregon grape, cherry, spirea, and bracken.

N. 1° 12' W., on W. bdy. of sec. 6.

Desc. 415 ft. over N. slope, through scattering timber and light undergrowth.

11.50 Enter dense vinemaple thicket, bears E. and W.

18.10 Spring branch, 1 lk. wide, course NE.; desc. 38 ft. over NE. slope.

19.30 Spring branch, 1 lk. wide, course N. 75° E.; desc. 260 ft. over NE. slope.

21.60 Leave vinemaple thicket and enter heavy timber and light undergrowth, bears E. and W.

32.38 A point 40.00 chs. in latitude from the cor. of secs. 1 and 12.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for 1/4 sec. cor. of sec. 1 only, with brass cap mkd.

1/4 S 1
|
1936

from which

A fir, 30 ins. diam., bears S. 40° W., 18 lks. dist., mkd. 1/4 S 1 B T.

A fir, 35 ins. diam., bears N. 33 1/2° W., 87 lks. dist., mkd. 1/4 S 1 B T.

Desc. 80 ft. over NE. slope.

36.30 Draw, drains N. 55° E.; along E. slope.

38.30 Small spur, slopes N. 50° E.; desc. 10 ft. over NE. slope.

40.01 The old 1/4 sec. cor. of secs. 1 and 6, which is a fir post, 24 x 3 x 3 ins. above ground, mkd. 1/4 S on W. face.

I change this cor. to refer to sec. 6 only.

At point for cor.,

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for 1/4 sec. cor. of sec. 6 only, with brass cap mkd.

|
1/4 S 6
1936

from which

A fir, 28 ins. diam., bears N. 66° E., 26 lks. dist., blaze healed; I do not open. I reblaze and re-mark this tree 1/4 S 6 B T. (Old B.T.)

A fir, 27 ins. diam., bears N. 76° W., 40 lks. dist., mkd. 1/4 S B T. I obliterate the marks. (Old B.T.)