

# County Surveyor's Record, Douglas County, Oregon

17629

Dependent Resurvey of W. Bdy. of T. 31 S., R. 2 E.

CHAINS

A white pine, 42 ins. diam., bears S. 42° E., 34 lks. dist., mkd. 1/4 S 6 B T. (New B.T.)

Thence

N. 0° 41' W., continuing measurements.

Desc. 115 ft. over NE. slope.

46.00 Draw, drains N. 85° E.; asc. 60 ft. over SE. slope.

49.40 Spur, slopes N. 80° E.; desc. 430 ft. over NE. slope.

71.04 Point for the cor. of Tps. 30 and 31 S., R. 1 E., hereinafter determined.

79.97 The old cor. of Tps. 30 and 31 S., Rs. 1 and 2 E., which is a porphyry stone, 24 x 9 x 8 ins., loosely set, mkd. with 6 notches on N. and W. edges.

I change this cor. to refer to Tps. 30 and 31 S., R. 2 E. only.

At point for cor.,

Set an iron post, 3 ft. long, 3 ins. diam., 27 ins. in the ground, for cor. of Tps. 30 and 31 S., R. 2 E., with brass cap mkd.

T 30 S	T 30 S
R 1 E	R 2 E
S 36	S 31
	S 6
	T 31 S
	1936

from which

A fir, 22 ins. diam., bears N. 32° E., 17 lks. dist., blaze healed; I do not open. I reblaze and re-mark this tree T 30 S R 2 E S 31 B T. (Old B.T.)

A white fir, 20 ins. diam., bears S. 39° E., 58 lks. dist., blaze healed; I do not open. (Old B.T.)

A fir, 22 ins. diam., bears S. 61° W., 30 lks. dist., mkd. T 31 S R 1 E S 1 B T. I obliterate the marks. (Old B.T.)

A hemlock, 20 ins. diam., bears N. 57° W., 7 lks. dist., mkd. in partially decayed blaze 30 1 E 3. I obliterate the marks. (Old B.T.)

A white pine, 47 ins. diam., bears S. 61° E., 85 lks. dist., mkd. T 31 S R 2 E S 6 B T. (New B.T.)

Land, mountainous.

Soil, sandy loam 2nd and 3rd rate.

Timber, fir, pine, cedar, hemlock, and yew.

Undergrowth, vinemaple, rhododendron, hazel, spirea, and bracken.

Retracement of part of Subdivisions of T. 31 S., R. 1 E.

"Retracement of the surveys executed by Fred Mensch, U.S. Cadastral Engineer, in 1923."

Retracement