

# County Surveyor's Record, Douglas County, Oregon

Retracement of Part of Subdivisions of T. 31 S., R. 1 E.

17630

CHAINS	
35.75 75.51	From the cor. of secs. 33 and 34 only, on S. bdy. of Tp. North, bet. secs. 33 and 34. Fall 14 lks. W. of 1/4 sec. cor. Fall 12 lks. W. of cor. of secs. 27, 28, 33, and 34.
40.00 80.00	From the cor. of secs. 27, 28, 33, and 34. North, bet. secs. 27 and 28. Fall 2 lks. E. of 1/4 sec. cor. Fall 12 lks. W. of cor. of secs. 21, 22, 27, and 28.
40.00 80.00	From the cor. of secs. 21, 22, 27, and 28. North bet. secs. 21 and 22. Fall 2 lks. E. of 1/4 sec. cor. Fall 10 lks. W. of cor. of secs. 15, 16, 21, and 22.
40.00 80.00	From the cor. of secs. 15, 16, 21, and 22. North, bet. secs. 15 and 16. Fall 2 lks. E. of 1/4 sec. cor. Fall 4 lks. E. of cor. of secs. 9, 10, 15, and 16.
40.00 80.00	From the cor. of secs. 9, 10, 15, and 16. North, bet. secs. 9 and 10. Fall 9 lks. W. of 1/4 sec. cor. Fall 15 lks. W. of cor. of secs. 3, 4, 9, and 10.
40.00 79.03	From the cor. of secs. 3, 4, 9, and 10. North, bet. secs. 3 and 4. Fall 14 lks. W. of 1/4 sec. cor. Fall 14 lks. W. of cor. of sec. 3, 4, 33, and 34, on N. bdy. of Tp.
<u>True Line</u>	
	From the cor. of secs. 33 and 34 only, on S. bdy. of T. 31 S., R. 1 E., previously described.
	N. 0° 13' E., bet. secs. 33 and 34.
	Desc. 290 ft. over NW. slope, changing to N. slope, through scattering timber and light undergrowth.
5.70	Creek, 2 lks. wide, course N. 40° E.; asc. 265 ft. over SE. slope.
14.00	Spur, slopes S. 60° E.; desc. 280 ft. over NE. slope, changing to N. slope.
20.00	Bluff, 30 ft. high, bears E. and E.
22.70	Draw, drains S. 40° E.; asc. 10 ft. over SE. slope.
23.70	Spur, slopes E.; desc. 130 ft. over NE. slope.
29.50	Elkhorn Creek, 15 lks. wide, course S. 40° E.; asc. 120 ft. over SW. slope; enter heavy timber, bears N. 40° W. and S. 40° E.
35.75	The 1/4 sec. cor. of secs. 33 and 34, which is an iron post, 1 in. diam., 10 ins. above ground, firmly set, mkd. and witnessed as described in the official record.
	Thence
	N. 0° 02' W., continuing measurements.
	Asc. 230 ft. over SW. slope.
45.30	Spur, slopes W.; desc. 60 ft. over NW. slope; enter scattering timber.