

County Surveyor's Record, Douglas County, Oregon

17638

Portion of Subdivisions of T. 31 S., R. 1 E

CHAINS

From the cor. of secs. 27, 28, 33, and 34, East on sectional correction line, setting temp. 1/4 sec. and sec. cors. at intervals of 40.00 chs. and at 239.88 chs. intersect the W. bdy. of T. 31 S., R. 2 E.

From the cor. of secs. 34 and 35 only, on S. bdy. of Tp., previously described.


N. 0° 05' E., bet. secs. 34 and 35.

Asc. 270 ft. over SW. slope, through scattering timber and dense undergrowth.

15.15 Spur, slopes W.; asc. 285 ft. over broken W. slope, changing to SW. slope.

29.85 Rocky point, slopes W.; desc. 10 ft. over W. slope.

34.42 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for 1/4 sec. cor., with brass cap mkd.



from which

A fir, 7 ins. diam., bears S. 33° E., 69 lks. dist., mkd. 1/4 S 35 B T.


A fir, 10 ins. diam., bears N. 73° W., 23 lks. dist., mkd. 1/4 S 34 B T.

Desc. 15 ft. over broken W. slope.

61.70 Dry creek bed, 4 lks. wide, course S. 15° W. from N. 10° W.; asc. 175 ft. over SW. slope.

74.42 Intersect sectional correction line, 10 lks. E. of temp. cor. of secs. 26, 27, 34, and 35.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of secs. 26, 27, 34, and 35, with brass cap mkd.



from which

A fir, 32 ins. diam., bears N. 35° E., 24 lks. dist., mkd. T 31 S R 1 E S 26 B T.

A fir, 7 ins. diam., bears S. 10° E., 74 lks. dist., mkd. T 31 S R 1 E S 35 B T.

A fir, 10 ins. diam., bears S. 12° W., 59 lks. dist., mkd. T 31 S R 1 E S 34 B T.

A fir, 42 ins. diam., bears N. 61° W., 82 lks. dist., mkd. T 31 S R 1 E S 27 B T.

Land, mountainous.
 Soil, sandy loam and rocky; 2nd and 4th rate.
 Timber, fir, pine, madrona, oak, cedar, chinquapin, and yew.
 Undergrowth, vinemapple, hazel, slickleaf, spirea, Oregon