

County Surveyor's Record, Douglas County, Oregon

Portion of Subdivisions of T. 31 S., R. 1 E. 17640

CHAINS	
29.40	Spur, slopes W.; desc. 60 ft. over NW. slope.
33.30	Spring branch, 1 lk. wide, course S. 25° W.; asc. 130 ft. over SE. slope.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for 1/4 sec. cor., with brass cap mkd.
	$\begin{array}{c} 1/4 \\ S\ 27 \ \ S\ 26 \\ \hline 1936 \end{array}$
	from which
	A fir, 20 ins. diam., bears S. 84° E., 76 lks. dist., mkd. 1/4 S 26 B T.
	A fir, 15 ins. diam., bears N. 42° W., 82 lks. dist., mkd. 1/4 S 27 B T.
	Asc. 75 ft. over SE. slope.
47.90	Small draw, drains SE.; asc. 175 ft. over SW. slope.
57.80	Spur, slopes SE.; asc. 215 ft. over SE. slope.
72.75	Ridge, bears NE. and SW.; asc. 22 ft. along W. slope.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of secs. 22, 23, 26, and 27, with brass cap mkd.
	$\begin{array}{c} T\ 31\ S \ \ R\ 1\ E \\ \hline S\ 22 \ \ S\ 23 \\ \hline S\ 27 \ \ S\ 26 \\ \hline 1936 \end{array}$
	from which
	A fir, 10 ins. diam., bears N. 34° E., 33 lks. dist., mkd. T 31 S R 1 E S 23 B T.
	A fir, 12 ins. diam., bears S. 64 1/2° E., 48 lks. dist., mkd. T 31 S R 1 E S 26 B T.
	A fir, 15 ins. diam., bears S. 18° W., 30 lks. dist., mkd. T 31 S R 1 E S 27 B T.
	A fir, 12 ins. diam., bears N. 42° W., 35 lks. dist., mkd. T 31 S R 1 E S 22 B T.
	Land, mountainous. Soil, sandy loam; 2nd and 3rd rate. Timber, fir, pine, yew, madrona, chinquapin, cedar, oak, and hamlock. Undergrowth, vinemaple, hazel, slickleaf, manzanita, Oregon grape, poison oak, and bracken.
	West, on a random line bet. secs. 22 and 27.
40.00	Set temp. 1/4 sec. cor.
80.16	Intersect N. and S. line, 2 lks. S. of cor. of secs. 21, 22, 27, and 28.
	Thence
	S. 89° 59' E., on true line bet. secs. 22 and 27.