

# County Surveyor's Record, Douglas County, Oregon

17647

Portion of Subdivisions of T. 31 S., R. 1 E.

CHAINS	
57.25	Spur, slopes NW.; desc. 10 ft. along N. slope, changing to NE. slope.
65.88	Spring branch, 1 lk. wide, course NW.; asc. 40 ft. over NW. slope.
70.30	Spur, slopes N. 30° W.; desc. 50 ft. over NE. slope.
80.16	The cor. of secs. 2, 3, 10, and 11.  Land, mountainous. Soil, sandy loam; 2nd rate. Timber, fir, cedar, hemlock, and yew. Undergrowth, vinemaple, spirea, hazel, and rhododendron.
40.00	N. 0° 05' E., on a random line bet. secs. 2 and 3.  Set temp. 1/4 sec. cor.
78.90	Intersect N. bdy. of Tp., 12 lks. W. of cor. of secs. 2, 3, 34, and 35, previously described.  Thence  S. 0° 10' W., on true line bet. secs. 2 and 3.  Asc. 60 ft. over NE. slope, changing to rolling W. slope, through heavy timber and light undergrowth.
25.70	Spur, slopes W.; desc. 45 ft. over SW. slope.
33.65	Creek, 2 lks. wide, course N. 75° W.; asc. 60 ft. over NE. slope.
38.90	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for 1/4 sec. cor., with brass cap mkd.  <div style="text-align: center; margin: 10px 0;"> <math display="block">\begin{array}{c} 1/4 \\   \\ S \ 3 \   \ S \ 2 \\ 1936 \end{array}</math> </div> <div style="text-align: right; margin-left: 100px;">from which</div> <p style="margin-left: 40px;">A fir, 35 ins. diam., bears N. 37° E., 31 lks. dist., mkd. 1/4 S 2 B T.</p> <p style="margin-left: 40px;">A white fir, 20 ins. diam., bears S. 50° W., 26 lks. dist., mkd. 1/4 S 3 B T.</p> <p style="margin-left: 40px;">Asc. 20 ft. over N. slope.</p>
42.15	Spur, slopes N. 30° W.; asc. 510 ft. over NW. slope.
60.00	Enter scattering timber and dense undergrowth, bears E. and W.
78.90	The cor. of secs. 2, 3, 10, and 11.  Land, mountainous. Soil, sandy loam; 2nd rate. Timber, fir, cedar, and hemlock. Undergrowth, vinemaple, rhododendron, spirea, and bracken.
	From the cor. of secs. 1, 2, 35, and 36, on S. bdy. of Tp.  N. 0° 06' E., bet. secs. 35 and 36.