

# County Surveyor's Record, Douglas County, Oregon

17648

Portion of Subdivisions of T. 31 S., R. 1 E.

CHAINS	
	<p>Asc. 340 ft. over SW. slope, through heavy timber and light undergrowth.</p>
20.50	<p>Ridge, bears N. 30° W. and S. 30° E.; desc. 55 ft. over gradual NE. slope.</p>
33.10	<p>Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for 1/4 sec. cor., with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <math display="block">\begin{array}{c} 1/4 \\   \\ S\ 35\   \ S\ 36 \\   \\ 1936 \end{array}</math> </div> <p style="text-align: right; margin-right: 100px;">from which</p> <p>A fir, 40 ins. diam., bears N. 61° E., 53 lks. dist., mkd. 1/4 S 36 B T.</p> <p>A fir, 40 ins. diam., bears N. 41° W., 73 lks. dist., mkd. 1/4 S 35 B T.</p> <p>Asc. 35 ft. along E. slope.</p>
52.00	<p>Top of ascent on E. slope; desc. 250 ft. over NE. slope.</p>
60.60	<p>Draw, drains E.; asc. 345 ft. over SE. slope.</p>
73.10	<p>Intersect sectional correction line, 2 lks. W. of the temp. cor. of secs. 25, 26, 35, and 36.</p> <p>Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of secs. 25, 26, 35, and 36, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <math display="block">\begin{array}{c} T\ 31\ S,\ R\ 1\ E \\ S\ 26\   \ S\ 25 \\ \hline S\ 35\   \ S\ 36 \\ 1936 \end{array}</math> </div> <p style="text-align: right; margin-right: 100px;">from which</p> <p>A fir, 7 ins. diam., bears N. 48° E., 28 lks. dist., mkd. T 31 S R 1 E S 25 B T.</p> <p>A fir, 6 ins. diam., bears S. 44 1/2° E., 42 lks. dist., mkd. T 31 S R 1 E S 36 B T.</p> <p>A fir, 47 ins. diam., bears S. 66° W., 50 lks. dist., mkd. T 31 S R 1 E S 35 B T.</p> <p>A fir, 6 ins. diam., bears N. 60° W., 30 lks. dist., mkd. T 31 S R 1 E S 26 B T.</p> <p>Land, mountainous. Soil, sandy loam and rocky; 2nd and 4th rate. Timber, fir, pine, yew, madrona, chinquapin, dogwood, oak, cedar, and hemlock. Undergrowth, vinemapple, hazel, willow, and bracken.</p>
	<p>From the cor. of secs. 26, 27, 34, and 35.</p> <p>East, on a sectional correction line, bet. secs. 26 and 35.</p> <p>Asc. 310 ft. over SW. slope, through heavy timber and dense undergrowth.</p>
10.20	<p>Ridge, bears N. 10° E. and S. 10° W.; desc. 80 ft. over SE. slope.</p>