

# County Surveyor's Record, Douglas County, Oregon

17650

Portion of Subdivisions of T. 31 S., R. 1 E.

CHAINS	
	$\frac{1}{4} \begin{array}{l} S\ 25 \\ S\ 36 \end{array}$ 1936
	from which
	A fir, 20 ins. diam., bears N. 72° E., 10 lks. dist., mkd. 1/4 S 25 B T.
	A fir, 12 ins. diam., bears S. 6° E., 22 lks. dist., mkd. 1/4 S 36 B T.
	Asc. 70 ft. over E. slope, changing to S. slope.
44.60	Draw, drains S. 10° E.; asc. 500 ft. over SE. slope.
65.25	Spur, slopes S. 10° E.; desc. 90 ft. over SW. slope.
70.50	Draw, drains S.; asc. 120 ft. over SE. slope.
79.90	The cor. of secs. 25, 26, 35, and 36.
	Land, mountainous. Soil, sandy loam and rocky; 2nd and 4th rate. Timber, fir, pine, yew, madrona, chinquapin, oak, and cedar. Undergrowth, vinemapple, hazel, slickleaf, manzanita, spirea, and bracken.
	N. 0° 06' E., bet. secs. 25 and 26.
	Asc. 40 ft. over SE. slope, through heavy timber and light undergrowth.
6.00	Small spur, slopes E.; desc. 65 ft. over NE. slope.
13.85	Head of draw, drains E.; asc. 240 ft. over SE. slope.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for 1/4 sec. cor., with brass cap mkd.
	$\frac{1}{4} \begin{array}{l}   \\ S\ 26 \quad   \quad S\ 25 \\   \\ 1936 \end{array}$
	from which
	A fir, 47 ins. diam., bears N. 41° E., 61 lks. dist., mkd. 1/4 S 25 B T.
	A fir, 37 ins. diam., bears S. 78° W., 67 lks. dist., mkd. 1/4 S 26 B T.
	Asc. 60 ft. over SE. slope.
47.30	Spur, slopes E.; desc. 90 ft. over NE. slope.
57.45	Small draw, drains N. 75° E.; asc. 40 ft. over SE. slope.
61.40	Spur, slopes E.; desc. 13 ft. over NE. slope.
64.55	Draw, drains E.; asc. 400 ft. over SE. slope.
79.00	Spur, slopes SE.; along E. slope.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of secs. 23, 24, 25, and 26, with brass