

County Surveyor's Record, Douglas County, Oregon

17652

Portion of Subdivisions of T. 31 S., R. 1 E.

CHAINS	
47.45	Spur, slopes S.; desc. 55 ft. over SE. slope.
50.30	Draw, drains S.; asc. 225 ft. over SW. slope.
58.40	Spur, slopes S. 10° W.; desc. 20 ft. over SE. slope.
59.95	Draw, drains S. 20° W.; asc. 175 ft. over W. slope.
65.00	Spur, slopes SW.; asc. 160 ft. over SW. slope.
71.31	Trail, Abbot Prairie to Butler Butte, bears N. and S.
73.75	Ridge, bears N. and S.; desc. 100 ft. over SE. slope.
79.00	Spur, slopes SE.; desc. 30 ft. over E. slope.
79.88	The cor. of secs. 23, 24, 25, and 26. Land, mountainous. Soil, sandy loam and rocky; 2nd and 4th rate. Timber, fir, pine, oak, madrona, cedar, and yew. Undergrowth, vinemaple, slickleaf, manzanita, spirea, hazel, and bracken.
	East, on a random line bet. secs. 24 and 25.
40.00	Set temp. 1/4 sec. cor.
79.94	Intersect E. bdy. of Tp., 12 lks. N. 0° 07' E. of cor. of secs. 24 and 25 only. Thence N. 89° 55' W., on true line bet. secs. 24 and 25. Desc. 315 ft. over W. slope, through heavy timber and dense undergrowth.
10.55	Head of draw, drains NW.; desc. 35 ft. over NW. slope.
12.00	Flat topped spur, slopes NW.; desc. 170 ft. over NW. slope.
19.30	Bitter Lick Creek, 18 lks. wide, course SW.; asc. 255 ft. over SE. slope, changing to E. slope.
19.96	Bitter Lick Way Trail, bears NE. and SW.
29.90	Spur, slopes SE.; asc. 270 ft. over SE. slope, changing to NE. slope.
39.94	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for 1/4 sec. cor., with brass cap mkd. <div style="text-align: center;">1/4 $\frac{S\ 24}{S\ 25}$ 1936</div> <div style="text-align: right;">from which</div> A fir, 27 ins. diam., bears N. 18° W., 37 lks. dist., mkd. 1/4 S 24 B T. A fir, 21 ins. diam., bears S. 52° W., 56 lks. dist., mkd. 1/4 S 25 B T.
	Asc. 250 ft. over NE. slope, changing to E. slope.
48.00	Spur, slopes S. 30° E.; desc. 45 ft. over SW. slope, chang- ing to broken S. slope.