

County Surveyor's Record, Douglas County, Oregon

17653

Portion of Subdivisions of T. 31 S., R. 1 E.

CHAINS	
57.50	Small spur, slopes S. 10° W.; desc. 140 ft. over SW. slope.
62.50	Draw, drains SE.; asc. 220 ft. over SE. slope.
70.20	Spur, slopes S. 60° E.; desc. 10 ft. over SW. slope.
72.90	Draw, drains SE.; asc. 60 ft. over E. slope.
74.45	Spur, slopes SE.; asc. 20 ft. over SE. slope.
76.10	Head of draw, drains SE.; asc. 180 ft. over E. slope.
79.94	The cor. of secs. 23, 24, 25, and 26.
	<p>Land, mountainous. Soil, sandy clay; 2nd and 3rd rate. Timber, fir, cedar, madrona, yew, pine, and chinquapin. Undergrowth, vinemaple, spirea, dogwood, manzanita, and bracken.</p>
	<p>N. 0° 06' E., bet. secs. 23 and 24.</p> <p>Asc. 380 ft. over SE. slope, through heavy timber and light undergrowth.</p>
13.80	Spur, slopes N. 80° E.; desc. 360 ft. over NE. slope.
23.80	Spring, drains E.; asc. 25 ft. over SE. slope.
26.55	Spur, slopes E.; desc. 345 ft. over NE. slope.
35.60	Spring branch, 1 lk. wide, course N. 80° E.; asc. 75 ft. over SE. slope.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for 1/4 sec. cor., with brass cap mkd.
	from which
	<p>A fir, 25 ins. diam., bears S. 60° E., 144 lks. dist., mkd. 1/4 S 24 B T.</p> <p>A sugar pine, 25 ins. diam., bears N. 48 1/2° W., 92 lks. dist., mkd. 1/4 S 23 B T.</p>
	Asc. 40 ft. over SE. slope.
42.25	Spur, slopes N. 60° E.; desc. 305 ft. over NE. slope, changing to N. slope.
51.41	Creek, 2 lks. wide, course N. 80° E.; asc. 50 ft. over SE. slope.
53.65	Spur, slopes N. 75° E.; desc. 50 ft. over NE. slope.
56.98	Creek, 5 lks. wide, course S. 80° E.; asc. 405 ft. over SW. slope, changing to S. slope.
74.90	Spur, slopes S. 75° W.; desc. 10 ft. over NW. slope.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of secs. 13, 14, 23, and 24, with brass cap mkd.