

# County Surveyor's Record, Douglas County, Oregon

17655

Portion of Subdivisions of T. 31 S., R. 1 E.

CHAINS	
57.55	Spring branch, 1 lks. wide, course SE.; asc. 135 ft. over SW. slope.
62.75	Spur, slopes S. 20° E.; desc. 245 ft. over E. slope.
69.50	Creek, 4 lks. wide, course S. 10° E.; asc. 10 ft. over SW. slope.
71.93	Spring branch, 1 lk. wide, course S. 30° W.; asc. 175 ft. over NW. slope.
79.86	The cor. of secs. 13, 14, 23, and 24.  Land, mountainous. Soil, sandy clay; 2nd and 3rd rate. Timber, fir, pine, yew, cedar, and chinquapin. Undergrowth, vinemaple, willow, spirea, manzanita, Oregon grape, slickleaf, rhododendron, and bracken.
	S. 89° 55' E., on a random line bet. secs. 13 and 24.
40.00	Set temp. 1/4 sec. cor.
79.62	Intersect E. bdy. of Tp., 26 lks. S. 0° 07' E. of cor. of secs. 13 and 24 only.  Thence  S. 89° 54' W., on true line bet. secs. 13 and 24.  Asc. 400 ft. over E. slope, through heavy timber and light undergrowth.
9.40	Spur, slopes S. 10° E.; desc. 165 ft. over SW. slope.
13.40	Enter dense undergrowth, bears N. and S.
20.13	Spring branch, 1 lk. wide, course S.; asc. 165 ft. over SE. slope.
26.25	Spur, slopes S.; desc. 30 ft. over SW. slope.
29.20	Small draw, drains S.; asc. 80 ft. over gradual SE. slope.
39.62	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for 1/4 sec. cor., with brass cap mkd.  $1/4 \frac{S \ 13}{S \ 24}$ 1936  from which  A fir, 7 ins. diam., bears N. 5° W., 76 lks. dist., mkd. 1/4 S 13 B T.  A fir, 12 ins. diam., bears S. 3 1/2° W., 151 lks. dist., mkd. 1/4 S 24 B T.  Asc. 135 ft. over SE. slope, changing to S. slope.
53.30	Spur, slopes S.; desc. 335 ft. over SW. slope, changing to W. slope.
62.60	Small draw, drains S. 30° W.; desc. 25 ft. over SW. slope.
65.65	Spur, slopes S.; desc. 325 ft. over W. slope; leave heavy undergrowth, bears N. and S.
79.62	The cor. of secs. 13, 14, 23, and 24.