

County Surveyor's Record, Douglas County, Oregon

17656

Portions of Subdivisions of T. 31 S., R. 1 E.

CHAINS

Land, mountainous.
Soil, sandy clay and rocky; 2nd and 4th rate.
Timber, fir, oak, madrona, chinquapin, Oregon maple, yew,
and pine.
Undergrowth, vinemaple, manzanita, willow, spirea, slick-
leaf, and bracken.

N. 0° 06' E., bet. secs. 13 and 14.

Desc. 65 ft. over NW. slope, through heavy timber and
dense undergrowth.

5.07 Spring branch, 1 lk. wide, course S. 60° W.; asc. 140 ft.
over S. slope.

9.40 Spur, slopes S. 30° W.; asc. 45 ft. over SW. slope, changing
to W. slope.

15.88 Spring branch, 1 lk. wide, course S. 50° W.; asc. 165 ft.
over SE. slope.

21.25 Spur, slopes SW.; asc. 55 ft. over broken W. slope.

31.07 Spring branch, 1 lk. wide, course SW.; asc. 300 ft. over
S. slope.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 21 ins. in the
ground to bedrock, and in a mound of stone to top, for
1/4 sec. cor., with brass cap mkd.

$$\begin{array}{c} 1/4 \\ | \\ \text{S } 14 \mid \text{S } 13 \\ | \\ 1936 \end{array}$$

from which

A fir, 20 ins. diam., bears S. 33° E., 32 lks. dist.,
mkd. 1/4 S 13 B T.

A pine, 35 ins. diam., bears S. 67° W., 61 lks. dist.,
mkd. 1/4 S 14 B T.

Asc. 55 ft. over S. slope.

41.85 Spur, slopes S. 30° W.; asc. 25 ft. over SW. slope, changing
to W. slope.

46.50 Draw, drains S. 30° W.; asc. 310 ft. over S. slope.

53.80 Spur, slopes S. 80° W.; asc. 365 ft. along rocky W. slope,
changing to SW. slope.

76.30 Ridge, bears N. 60° W. and S. 60° E.; desc. 90 ft. over NE.
slope.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the
ground, for cor. of secs. 11, 12, 13, and 14, with brass
cap mkd.

$$\begin{array}{c} \text{T } 31 \text{ S } \mid \text{R } 1 \text{ E} \\ \text{S } 11 \mid \text{S } 12 \\ \text{S } 14 \mid \text{S } 13 \\ 1936 \end{array}$$

from which

A white fir, 10 ins. diam., bears N. 70° E., 21 lks.
dist., mkd. T 31 S R 1 E S 12 B T.