

County Surveyor's Record, Douglas County, Oregon

17659

Portion of Subdivisions of T. 31 S., R. 1 E.


CHAINS

37.70

Spur, slopes E.; desc. 40 ft. over NE. slope.

40.00

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for 1/4 sec. cor., with brass cap mkd.



from which

A fir, 8 ins. diam., bears N. 34° E., 44 lks. dist., mkd. 1/4 S 12 B T.

A fir, 10 ins. diam., bears N. 51° W., 58 lks. dist., mkd. 1/4 S 11 B T.

Desc. 35 ft. along E. slope, changing to NE. slope.

46.00

Draw, drains S. 75° E.; asc. 90 ft. over SE. slope.

54.45

Draw, drains SE.; asc. 885 ft. over S. slope.

59.00

Top of bluff, 85 ft. high, bears E. and W.

72.00

Leave dense undergrowth.

77.10


Divide bet. South Umpqua River and Rogue River, bears E. and W.; desc. 30 ft. over N. slope.

79.06

Forest Service Road and Telephone line, bears E. and W.

80.00

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of secs. 1, 2, 11, and 12, with brass cap mkd.



from which

A white fir, 9 ins. diam., bears N. 3° E., 126 lks. dist., mkd. T 31 S R 1 E S 1 B T.

A fir, 10 ins. diam., bears S. 78° E., 38 lks. dist., mkd. T 31 S R 1 E S 12 B T.

A fir, 37 ins. diam., bears S. 43° W., 154 lks. dist., mkd. T 31 S R 1 E S 11 B T.

A fir, 7 ins. diam., bears N. 87° W., 71 lks. dist., mkd. T 31 S R 1 E S 2 B T.

Land, mountainous.

Soil, sandy clay and rocky; 2nd and 4th rate.

Timber, fir, pine, cedar, and yew.

Undergrowth, willow, hazel, rhododendron, vinemapple, spirea, and bracken.

40.00

S. 89° 59' W., on a random line bet. secs. 2 and 11.

Set temp. 1/4 sec. cor.

79.98

Intersect N. and S. line, 12 lks. N. of cor. of secs. 2, 3, 10, and 11.

Thence