

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of North Boundary
 (Fifth Standard Parallel South),
 T. 23 S., R. 5 W., Willamette Meridian, Oregon 17666

CHAINS

1/4	S 4
T 23 S	R 5 W
SC	
1983	

FOOK 2-94
M118-66

from which

A fir, 8 ins. diam., bears S. 34 3/4° E., 105 lks.
dist., mkd. 1/4 S4 SC BT.

A cedar, 10 ins. diam., bears S. 80° W., 88 lks.
dist., mkd. 1/4 S4 SC BT.

From this point, the 1/4 sec. cor. of sec. 35 only, T. 22 S., R. 5 W., bears S. 89° 54' E., 155.24 chs. dist., perpetuated and recorded by Ben B. Irving, Deputy County Surveyor, in 1940, from original evidence no longer in existence, monumented with an iron pipe, 1 1/4 ins. diam., firmly set, projecting 4 ins. above ground, from which the remains of bearing trees mkd. by Irving

An oak, 8 ins. diam., bears N. 62 1/4° E., 46 lks.
dist., with healed blaze.

A fir snag, 15 ins. diam., bears N. 85 1/4° W.,
40 lks. dist., with scribe marks 1/4 S33 BT
visible on bark blaze.

At the corner point

Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 22 S	R 5 W
1/4	S 35
T 23 S	R 5 W

1983

FOOK 2-94
M118-66

from which a new bearing tree

An oak, 6 ins. diam., bears N. 23° W., 61 lks.
dist., mkd. 1/4 S 35 BT.

From this same point, the standard 1/4 sec. cor. of sec. 1, bears S. 89° 54' E., 240.09 chs. dist., perpetuated and recorded by Ben B. Irving, Deputy County Surveyor, in 1940, and further perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1960, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 22 S	R 5 W
North 1/4	
S 1	
T 23 S	R 5 W

1960

from which the original bearing trees

An oak, 28 ins. diam., bears S. 46 1/2° E.,
100 lks. dist., with opened blaze, no
marks visible.