

# County Surveyor's Record, Douglas County, Oregon

17667

Dependent Resurvey, Portion of North Boundary  
(Fifth Standard Parallel South),  
T. 23 S., R. 5 W., Willamette Meridian, Oregon

**CHAINS**

An oak, 42 ins. diam., bears S. 36° W.,  
55 lks. dist., with opened blaze, no  
marks visible.

and a bearing tree mkd. by Irving

An oak, 11 ins. diam., bears S. 34 1/2° W.,  
13 lks. dist., with healed double blaze.

and a bearing tree mkd. by Byron

A fir, 16 ins. diam., bears S. 59 3/4° E.,  
55 lks. dist., with healed double blaze.

From this same point, a locally established point, bears  
S. 38° 34' W., 0.271 chs. dist., monumented with an iron  
rod, 1/2 in. diam., firmly set, projecting 4 ins. above  
ground, from which remains of bearing trees mkd. by  
person(s) unknown

A fir, 12 ins. diam., bears S. 70 3/4° E.,  
47 lks. dist., with scribe marks 1/4 S visible  
on partially healed double blaze.

A fir, 11 ins. diam., bears S. 33 1/2° W.,  
50 lks. dist., with scribe marks 1/4 S4 visible  
on partially healed double blaze.

An oak snag, 17 ins. diam., bears N. 74 3/4° W.,  
22 lks. dist., with scribe marks 1/4 S visible  
on opened blaze.

From this same point, Oregon State Highway Department  
station P444, set in 1952, bears S. 57° 05' E.,  
69.577 chs. dist., monumented with a bronze disc, 3 1/2 ins.  
diam., set flush in bottom step on W. entrance of  
City Hall, Yoncalla, Oregon, with top mkd. P444 1952.

N. 89° 54' W., on the N. bdy. of sec. 4, marking and  
blazing the true line.

Descend over SW. slope, through heavy timber and dense  
undergrowth.

0.20 Creek, 6 lks. wide, course S. 15° E.; asc. over broken  
NE. slope.

4.87 Point for the 1/4 sec. cor. of sec. 33 only, T. 22 S.,  
R. 5 W., at proportionate distance; there is no remaining  
evidence of the original corner, described in the field  
notes of the subdivision of sec. 33, T. 22 S., R. 5 W.,  
executed concurrently under this same Group.

Ascend over NE. slope, changing to SE. slope.

17.25 Spur, slopes S. 20° W.; asc. over SE. slope.

19.57 From this point, an oak, 30 ins. diam., bears South,  
0.115 chs. dist., with original line blazes made by Elder  
and Gile in 1853, that indicate line is to the north, and  
recorded as a line tree by Gordon and Gardner in 1855,  
with 2 hacks on the E. and W. faces; this tree is treated  
as an off-line junior corner in this resurvey.

24.89 Point for the W 1/16 sec. cor. of sec. 33 only, T. 22 S.,  
R. 5 W., described in the field notes of the subdivision  
of sec. 33, T. 22 S., R. 5 W., executed concurrently  
under this same Group.

SEE HAINES  
F.O. #110