

County Surveyor's Record, Douglas County, Oregon

17669

Dependent Resurvey, Portion of North Boundary
(Fifth Standard Parallel South),
T. 23 S., R. 5 W., Willamette Meridian, Oregon

CHAINS

39.49

The standard 1/4 sec. cor. of sec. 5, perpetuated and recorded by Wilford N. Haines, Registered Land Surveyor, No. 239, in 1960, monumented with a "T" shaped iron rod, 1 in. diam., firmly set, projecting 4 ins. above ground, with steel washer, 1 in. diam., mkd. Wilford N. Haines 239 Survey Point Drain, Ore., from which the remaining original bearing tree

A fir, 45 ins. diam., bears S. 28° W., 204 lks. dist., with scribe marks 4S visible on opened blaze.

and a bearing tree mkd. by Haines

A fir, 24 ins. diam., bears S. 30° W., 53 lks. dist., with scribe marks 1/4 S5 B T visible on bark blaze.

At the corner point

Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

OK
 2-94 1/18/66

1/4	S	5
T 23 S	R 5 W	SC

1982

from which a new bearing tree

A fir, 8 ins. diam., bears S. 52 1/2° E., 75 lks. dist., mkd. 1/4 S5 SC BT.

Deposit iron rod alongside iron post.

S. 89° 59' W., beginning new measurement.

Ascend over broken SE. slope.

3.65

Ridge, bears N. 55° E. and S. 45° W.; desc. over broken NW. slope.

4.85

From this point, the 1/4 sec. cor. of sec. 32 only, T. 22 S., R. 5 W., bears North, 0.04 chs. dist., perpetuated and recorded by Wilford N. Haines, Registered Land Surveyor, No. 239, in 1960, monumented with a "T" shaped iron rod, 1 in. diam., firmly set, projecting 8 ins. above ground, from which the remains of an original bearing tree

A decayed fir stump, size indeterminate, bears N. 15° E., 21 lks. dist., no marks visible.

and the remains of a bearing tree mkd. by Haines

A fir snag, 13 ins. diam., bears S. 85° W., 20 lks. dist., with scribe marks 1/4 S BT visible on open blaze.

and a bearing tree mkd. by person(s) unknown

A fir, 37 ins. diam., bears N. 21° E., 40 lks. dist., with healed double blaze.

No new monument established.