

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of North Boundary
(Fifth Standard Parallel South),
T. 23 S., R. 5 W., Willamette Meridian, Oregon

17670

CHAINS

6.25

Gravelled road, 25 lks. wide, bears N. 35° E. and S. 30° W.

39.60

Point for the standard cor. of secs. 5 and 6, at proportionate distance based on the 1855 Gordon and Gardner resurvey; there is no remaining evidence of the original corner.

Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with aluminum cap mkd.

S 6	S 5
T 23 S	R 5 W

SC

1982

from which

A fir, 18 ins. diam., bears S. 7 1/2° E., 67 lks. dist., mkd. T23S R5W S5 SC BT.

A fir, 14 ins. diam., bears S. 11° W., 57 lks. dist., mkd. T23S R5W S6 SC BT.

From this point, the cor. of secs. 31 and 32 only, T. 22 S., R. 5 W., bears S. 88° 17' W., 5.14 chs. dist., perpetuated and recorded by Oscar F. Thiel, Deputy County Surveyor, in 1901, from original evidence no longer in existence, and further perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1958, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 22 S		
S 31	S 32	R
S 6		5
		W

T 23 S

1958

from which the remains of bearing trees mkd. by Byron

A sawed fir stump, 26 ins. diam., bears N. 73° E., 73 lks. dist., with healed double blaze.

A sawed fir stump, 8 ins. diam., bears S. 45 3/4° E., 55 lks. dist., with healed blaze.

A fir, 10 ins. diam., bears N. 12 3/4° W., 12 1/2 lks. dist., with healed double blaze.

From this same point, an original line tree, bears S. 89° 59' W., 32.80 chs. dist., an oak, 37 ins. diam., mkd. with 2 notches on E. and W. faces, from which bearing trees mkd. by person(s) unknown

A fir, 8 ins. diam., bears S. 81 1/2° E., 74 lks. dist., with scribe marks X BT visible on open blaze.