

County Surveyor's Record, Douglas County, Oregon

17671

Dependent Resurvey, Portion of North Boundary
(Fifth Standard Parallel South),
T. 23 S., R. 5 W., Willamette Meridian, Oregon

CHAINS

An oak, 11 ins. diam., bears N. 35° W., 46 1/2 lks. dist., with scribe marks X BT visible on open blaze.

From this same point, a point established and recorded by Wilford N. Haines, Registered Land Surveyor, No. 239, in 1960, bears N. 45° 51' W., 0.047 chs. dist., monumented with a "T" shaped iron rod, 1 in. diam., firmly set, projecting 9 ins. above ground, from which a bearing tree mkd. by Haines

A fir, 17 ins. diam., bears S. 1° E., 40 lks. dist., with healed blaze.

Land, mountainous.

Soil, rocky clay.

Timber, fir, hemlock, cedar, yew, maple, oak, madrone, alder, and ash; undergrowth, Oregon grape, salal, ferns, hazel, arrowwood, blackberry, huckleberry, and young timber.

Dependent Resurvey of
a Portion of the Subdivisional Lines,
T. 23 S., R. 5 W., Willamette Meridian, Oregon

(Restoring the survey
by Robert Elder and Henry S. Gile in 1853)

From the 1/4 sec. cor. of secs. 5 and 8, perpetuated and recorded by Oscar F. Thiel, Deputy County Surveyor, in 1900, from original evidence no longer in existence, and further perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1960, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 23 S R 5 W

1/4 $\frac{S 5}{S 8}$

1960

from which bearing trees mkd. by Byron

An oak, 18 ins. diam., bears N. 87 1/2° W., 39 1/2 lks. dist., with healed double blaze.

A white oak, 20 ins. diam., bears N. 10 1/2° W., 39 1/2 lks. dist., with healed double blaze.

and a new bearing tree

A fir, 12 ins. diam., bears S. 54 1/4° E., 187 lks. dist., mkd. 1/4 S8 BT.

N. 89° 25' W., bet. secs. 5 and 8, marking and blazing the true line.