

County Surveyor's Record, Douglas County, Oregon

17672

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 23 S., R. 5 W., Willamette Meridian, Oregon

CHAINS											
	Ascend over broken SE. slope, through heavy timber and dense undergrowth.										
16.50	Spur, slopes S. 5° W.; desc. over SW. slope.										
19.88	Point for W 1/16 sec. cor. of secs. 5 and 8. Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd. <div style="text-align: center;"> $W \frac{1}{16} \frac{S \ 5}{S \ 8}$ </div> <p style="text-align: center;">1982</p> from which A fir, 22 ins. diam., bears S. 5 1/4° W., 16 lks. dist., mkd. W 1/16 S8 BT. A fir, 12 ins. diam., bears N. 8° W., 36 lks. dist., mkd. W 1/16 S5 BT. From this point, a locally established point, bears N. 38° 40' W., 0.013 chs. dist., monumented with an iron pipe, 1 in. diam., firmly set, projecting 12 ins. above ground, from which bearing tree mkd. by person(s) unknown A fir, 11 ins. diam., bears N. 60° E., 32 lks. dist., with healed blaze. Descend over SW. slope.										
23.10	Ravine, drains S. 30° W.; asc. over SE. slope.										
29.65	Spur, slopes S. 30° W.; desc. over SW. slope.										
39.76	The cor. of secs. 5, 6, 7, and 8, perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1956, from original evidence no longer in existence, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd. <div style="text-align: center;"> <p>COUNTY SURVEYORS OFFICE</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T 23 S</td> <td style="border-left: 1px solid black; border-right: 1px solid black; padding: 0 10px;">R 5 W</td> <td style="padding: 0 10px;"></td> </tr> <tr> <td style="padding: 0 10px;">SEC</td> <td style="border-left: 1px solid black; border-right: 1px solid black; text-align: center;"> <table style="border-collapse: collapse;"> <tr> <td style="border-bottom: 1px solid black; padding: 0 5px;">S 6</td> <td style="border-bottom: 1px solid black; padding: 0 5px;">S 5</td> </tr> <tr> <td style="padding: 0 5px;">S 7</td> <td style="padding: 0 5px;">S 8</td> </tr> </table> </td> <td style="padding: 0 10px;">COR</td> </tr> </table> <p style="margin-top: 5px;">1956</p> </div> <div style="text-align: right; margin-top: 10px;"> <p><i>Fd. 3/90</i> <i>K. Hoffine</i> <i>C.S. 63/104</i> <i>FD 02 12/93</i> <i>Dist. 12/93</i> <i>For 12/93</i> <i>11843</i></p> </div> from which the remains of bearing trees mkd. by Byron A black oak, 28 ins. diam., bears N. 24 1/4° E., 109 lks. dist., with healed blaze. A fir stump, 30 ins. diam., bears S. 12 1/2° E., 68 lks. dist., with healed blaze. An oak, 25 ins. diam., bears S. 10 1/2° W., 119 lks. dist., with healed blaze. and new bearing trees A fir, 6 ins. diam., bears S. 45 1/2° E., 38 lks. dist., mkd. T23S R5W S8 BT. A white oak, 14 ins. diam., bears N. 17 3/4° W., 375 lks. dist., mkd. T23S R5W S6 BT.	T 23 S	R 5 W		SEC	<table style="border-collapse: collapse;"> <tr> <td style="border-bottom: 1px solid black; padding: 0 5px;">S 6</td> <td style="border-bottom: 1px solid black; padding: 0 5px;">S 5</td> </tr> <tr> <td style="padding: 0 5px;">S 7</td> <td style="padding: 0 5px;">S 8</td> </tr> </table>	S 6	S 5	S 7	S 8	COR
T 23 S	R 5 W										
SEC	<table style="border-collapse: collapse;"> <tr> <td style="border-bottom: 1px solid black; padding: 0 5px;">S 6</td> <td style="border-bottom: 1px solid black; padding: 0 5px;">S 5</td> </tr> <tr> <td style="padding: 0 5px;">S 7</td> <td style="padding: 0 5px;">S 8</td> </tr> </table>	S 6	S 5	S 7	S 8	COR					
S 6	S 5										
S 7	S 8										