

# County Surveyor's Record, Douglas County, Oregon

17673 Dependent Resurvey, Portion of the Subdivisional Lines,  
T. 23 S., R. 5 W., Willamette Meridian, Oregon

**CHAINS**

Land, mountainous.  
Soil, rocky clay.  
Timber, fir, cedar, yew, oak, hemlock, madrone, ash, alder, and chinquapin; undergrowth, poison oak, Oregon grape, hazel, salal, arrowwood, blackberry, thimbleberry, huckleberry, wild rose, ferns, and young timber.

N. 1° 10' E., bet. secs. 5 and 6.

Ascend over broken SW. slope, through heavy timber and dense undergrowth.


13.40 Spur, slopes W.; desc. over NW. slope.

16.30 Ravine, drains W.; asc. over SW. slope.

19.88 Point for the S 1/16 sec. cor. of secs. 5 and 6.

Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

*Fd. 10/90 c s 63/104*



from which

A fir, 13 ins. diam., bears S. 52° E., 13 lks. dist., mkd. S 1/16 S5 BT.

A fir, 11 ins. diam., bears N. 63° W., 15 1/2 lks. dist., mkd. S 1/16 S6 BT.

From this point, a point established and recorded by Wilford N. Haines, Registered Land Surveyor No. 239, in 1960, bears N. 25° 30' E., 0.086 chs. dist., monumented with a "T" shaped iron rod, 1 in. diam., firmly set, projecting 6 ins. above the ground, with steel washer mkd. Wilford N. Haines Drain Ore. Survey Point 239, from which bearing trees mkd. by Haines

A fir, 31 ins. diam., bears N. 7 1/2° E., 45 lks. dist., with scribe marks 1/16 S BT visible on bark blaze.

A fir, 29 ins. diam., bears N. 54° W., 40 lks. dist., with scribe marks 1/16 S BT visible on bark blaze.

Ascend over SW. slope.

33.65 Spur, slopes S. 50° W.; desc. over SW. slope.

36.35 Ravine, drains N. 85° W.; asc. over NW. slope.

39.76 Point for the 1/4 sec. cor. of secs. 5 and 6, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

*Fd 4/90 c s 63/104*

