

County Surveyor's Record, Douglas County, Oregon

17675

Subdivision of Section 5,
T. 23 S., R. 5 W., Willamette Meridian, Oregon

CHAINS

From the 1/4 sec. cor. of secs. 4 and 5, perpetuated and recorded by Oscar F. Thiel, Deputy County Surveyor, in 1885, from original evidence no longer in existence, and further perpetuated and recorded by Vernon R. Tracy, Deputy County Surveyor, in 1969, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 9 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

1/4 S 5 | S 4

1969

from which bearing tree mkd. by person(s) unknown

An ash, 16 ins. diam., bears N. 15° E., 25 lks. dist., with scribe marks 1/4 S5 CS BT visible on open blaze.

and a reference monument established by Tracy

An iron rod, 3/4 in. diam., firmly set, projecting 1 in. above ground, bears S. 87 1/2° E., 21 lks. dist.

and a new reference monument

An aluminum post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 15° E., 27 lks. dist., with aluminum cap mkd. 1/4 S4 RM 1982 and an arrow pointing to the corner.

The corner is located in woven wire fence, extending N. and S.

S. 89° 59' W., on the E. and W. center line of sec. 5.

Ascend over broken NE. slope, through open grassland.

24.00 Leave grassland, enter heavy timber and dense undergrowth, edge bears N. and S.

40.10 The center 1/4 sec. cor. of sec. 5.

Ascend over broken NE. slope.

51.80 Gravelled road, 25 lks. wide, bears N. 10° E. and S. 10° W.

52.35 Ridge, bears N. 10° W. and S. 10° E.; desc. along S. slope.

58.05 Spur, slopes S. 85° W.; desc. along spur on SW. slope.

59.94 Point for the center W 1/16 sec. cor. of sec. 5.

Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

C ———— W 1/16 ———— C
 S 5

1982

from which