

County Surveyor's Record, Douglas County, Oregon

17676

Subdivision of Section 5,
T. 23 S., R. 5 W., Willamette Meridian, Oregon

CHAINS	
	N. 1° 02' E., on the N. and S. center line of sec. 5.
	Ascend over broken SE. slope, through heavy timber and dense undergrowth.
5.05	Spur, slopes E.; asc. over broken SE. slope.
20.08	Point for the center S 1/16 sec. cor. of sec. 5.
	Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.
	$ \begin{array}{c} C \\ \\ S \ 1/16 \ \ S \ 5 \\ \\ C \\ 1982 \end{array} $
	from which
	A fir, 6 ins. diam., bears S. 48 1/4° E., 81 lks. dist., mkd. CS 1/16 S5 BT.
	A fir, 14 ins. diam., bears N. 35 3/4° W., 52 lks. dist., mkd. CS 1/16 S5 BT.
	Ascend over broken SE. slope.
31.55	Spur, slopes S. 50° E.; desc. over broken NE. slope.
39.40	Woven wire fence, extends E. and W.
40.16	Point for the center 1/4 sec. cor. of sec. 5, at intersection with the E. and W. center line.
	Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.
	$ \begin{array}{cc} T \ 23 \ S & R \ 5 \ W \\ \\ C \ 1/4 & S \ 5 \\ \\ 1982 \end{array} $
	from which
	A fir, 5 ins. diam., bears S. 45 1/2° E., 10 1/2 lks. dist., mkd. X BT.
	A fir, 8 ins. diam., bears N. 60° W., 8 1/2 lks. dist., mkd. C 1/4 S5 BT.
	Descend over broken NE. slope.
42.05	Ravine, drains N. 85° E.; asc. over SE. slope.
43.85	Spur, slopes N. 70° E.; desc. over NE. slope.
46.30	Ravine, drains E.; asc. over SE. slope.
52.80	Spur, slopes N. 65° E.; desc. over NE. slope.
61.60	Ravine, drains N. 80° E.; asc. over broken SE. slope.
79.18	The standard 1/4 sec. cor. of sec. 5, on the N. bdy. of the Tp.