

# County Surveyor's Record, Douglas County, Oregon

17877

Subdivision of Section 5,  
T. 23 S., R. 5 W., Willamette Meridian, Oregon

CHAINS	
	<p style="text-align: center;">A fir, 10 ins. diam., bears S. 21° E., 98 lks. dist., mkd. CW 1/16 S5 BT.</p> <p style="text-align: center;">A fir, 18 ins. diam., bears S. 67 1/2° W., 44 lks. dist., mkd. CW 1/16 S5 BT.</p>
65.20	Gravelled road, 20 lks. wide, bears N. 60° E. and N. 80° W.
66.95	Spur, slopes N. 80° W.; desc. over NW. slope.
77.25	Spur, slopes S. 50° W.; desc. over NW. slope.
76.96	Head of ravine, drains N. 5° W.; asc. over NE. slope.
79.78	The 1/4 sec. cor. of secs. 5 and 6.
	<p style="text-align: center;">From the 1/16 sec. cor. of secs. 5 and 8.</p> <p style="text-align: center;">N. 1° 07' E., on the N. and S. center line of the SW 1/4 of sec. 5.</p> <p style="text-align: center;">Descend over NW. slope, through heavy timber and dense undergrowth.</p>
5.05	Ravine, drains S. 60° W.; asc. over SW. slope.
8.10	Spur, slopes S. 60° W.; desc. over NW. slope.
15.60	Ravine, drains S. 70° W.; asc. over NW. slope.
19.98	<p>Point for the SW 1/16 sec. cor. of sec. 5, at intersection with the E. and W. center line of the SW 1/4.</p> <p>Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in ground, with aluminum cap mkd.</p>
	<p><i>Ed. 4/90 CS 63/04</i>                      SW 1/16    S 5</p> <p style="text-align: center;">1982</p>
	<p>from which</p> <p style="text-align: center;">A fir, 12 ins. diam., bears S. 24 1/2° E., 27 lks. dist., mkd. SW 1/16 S5 BT.</p> <p style="text-align: center;">A fir, 5 ins. diam., bears N. 49° W., 24 lks. dist., mkd. X BT.</p> <p>From this point, a locally established point, bears N. 33° 30' E., 0.065 chs. dist., monumented with an iron pipe, 1 1/2 ins. diam., firmly set, projecting 8 ins. above the ground, from which a bearing tree mkd. by person(s) unknown</p> <p style="text-align: center;">A fir, 15 ins. diam., bears N. 42 1/2° E., 51 lks. dist., with healed double blaze.</p> <p>The corner is located on spur, slopes S. 65° W.</p> <p>Descend over broken NW. slope.</p>
33.15	Ravine, drains S. 65° W.; asc. over broken SW. slope.
39.96	The center W 1/16 sec. cor. of sec. 5.