

# County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of the Subdivisional Lines, **17684**  
T. 22 S., R. 5 W., Willamette Meridian, Oregon

CHAINS					
	<p>An iron post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 60° W., 113 1/2 lks. dist., with brass cap mkd. T22S R5W S33 RSM 75 FT 1982 and an arrow pointing to the corner.</p> <p>The corner is located 1.30 chs. west of State Highway No. 99, paved, 50 lks. wide, bears N. 20° W. and S. 20° E.</p> <p>S. 89° 00' W., bet. secs. 28 and 33.</p> <p>Ascend over NE. slope, through pasture.</p>				
1.20	Enter timber, edge bears N. 5° E. and S. 5° W.				
4.85	Dirt road, 20 lks. wide, bears N. 30° W. and S. 30° E.				
8.95	Spur, slopes N. 20° E.; desc. over NW. slope, also dirt road, 15 lks. wide, bears N. 20° E. and S. 20° W.				
20.055	<p>Point for the E 1/16 sec. cor. of secs. 28 and 33.</p> <p>Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td style="padding: 0 10px;">E 1/16</td> <td style="border: 1px solid black; padding: 0 5px;">S 28</td> </tr> <tr> <td></td> <td style="border: 1px solid black; padding: 0 5px;">S 33</td> </tr> </table> <p>1982</p> </div> <p>from which</p> <p style="padding-left: 40px;">A fir, 18 ins. diam., bears N. 48 1/2° E., 25 1/2 lks. dist., mkd. E 1/16 S28 BT.</p> <p style="padding-left: 40px;">A fir, 4 ins. diam., bears S. 47 1/2° W., 37 lks. dist., mkd. X BT.</p> <p>Descend over NW. slope.</p>	E 1/16	S 28		S 33
E 1/16	S 28				
	S 33				
25.95	Creek, 5 lks. wide, course N. 40° E.; asc. over SE. slope.				
34.80	Spur, slopes S. 20° W.; desc. over SW. slope.				
36.90	Creek, 6 lks. wide, course S. 40° E.; asc. over SE. slope.				
40.11	<p>The 1/4 sec. cor. of secs. 28 and 33, reestablished by proportionate measurement and recorded by Eugene A. Bloom, Registered Land Surveyor, No. 492, in 1980, and is accepted as the best available evidence of the position of the original corner, monumented with an iron rod, 5/8 in. diam., firmly set, projecting 6 ins. above ground, from which bearing trees mkd. by Bloom</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears N. 29° E., 57 lks. dist., with scribe marks 1/4 S28 BT visible on open double blaze.</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears S. 33° E., 65 lks. dist., with scribe marks 1/4 S33 BT visible on open double blaze.</p> <p>At the corner point</p> <p>Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in ground, with aluminum cap mkd.</p>				